

General Information

| | |
|-------------------------------|-------------------|
| Extended Product Type: | JB22-5 |
| Product ID: | 1SNK922305R0000 |
| EAN: | 3472599163621 |
| Catalog Description: | JB22-5 Jumper Bar |
| Long Description: | Screw jumper bars |

Additional Information

| | |
|---|---|
| ABB Industrial IT Suite: | Control IT |
| ATEX Certificate: | 1SND162004A1707 |
| Ambient Air Temperature: | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| Ambient Temperature: | -5 ... +40 °C |
| CB Certificate: | 1SND161034A0202 |
| Country of Origin: | France (FR) |
| Customs Tariff Number: | 85369010 |
| Data Sheet, Technical Information: | 1SNK160033D0201 |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Dielectric Test Voltage: | 2200 V |
| E-nummer: | 2925395 |
| EAN: | 3472599163621 |
| ETIM 4: | EC000489 - Cross-connector for terminal block |
| ETIM 5: | EC000489 - Cross-connector for terminal block |
| ETIM 6: | EC000489 - Cross-connector for terminal block |
| Function: | Jumper Bars |
| IIT Publishing Status: | Level 0 - Information enabled |
| Industrial IT Certification Level: | 0 |
| Instructions and Manuals: | 1SNK160027C0201 |
| Insulation Material: | Polyamide |
| Invoice Description: | JB22-5 Jumper Bar |
| Maximum Operating Voltage UL/CSA: | Main Circuit 600 V |
| Medium Description: | Screw jumper bars |
| Minimum Order Quantity: | 5 piece |
| Mounting Type: | - With flat pliers, cut out the partitions on the terminal block insulating body. Be careful to not cut out the jumpered terminal blocks partitions at both ends of the assembly in order to maintain the IP20, Nema1 protection and insulation, - Install the jumper bar with the recommended tool and torque. |
| Number of Poles: | 5 |
| Object Classification Code: | X |
| Order Multiple: | 5 piece |
| Package Level 1 EAN: | 3472599163621 |
| Package Level 1 Gross Weight: | 0.38 kg |
| Package Level 1 Height: | 45 mm |
| Package Level 1 Length: | 105 mm |
| Package Level 1 Units: | 5 piece |
| Package Level 1 Width: | 45 mm |
| Package Level 2 Gross Weight: | 8.23 kg |

| | |
|--|---|
| Package Level 2 Height: | 200 mm |
| Package Level 2 Length: | 300 mm |
| Package Level 2 Units: | 105 piece |
| Package Level 2 Width: | 200 mm |
| Package Level 3 Units: | 10080 piece |
| Power Loss: | 6.1 W |
| Product Main Type: | JB22 |
| Product Name: | Jumper Bar |
| Product Net Depth: | 20.7 mm |
| Product Net Height: | 101 mm |
| Product Net Length: | 20.7 mm |
| Product Net Weight: | 76.1 g |
| Product Net Width: | 22 mm |
| Product Packing Type: | Box |
| Rated Current (I_n): | Main Circuit 192 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 8000 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 8400 A |
| Rated Voltage (U_r): | 1000 V |
| Recommended Screw Driver: | 4 mm |
| RoHS Date: | 18 08 2005 |
| RoHS Information: | 1SND230499F0202 |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Selling Unit of Measure: | piece |
| Short Description: | Jumper Bars JB22-5 |
| Spacing: | 22 mm |
| Sub-Function 2: | Screw |
| Suitable For: | D70/22 ZS70 |

