

# XT2N 160 Ekip I In=63A 3p F F



Products → Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

## General Information

<b>Extended Product Type:</b>	XT2N 160 Ekip I In=63A 3p F F
<b>Product ID:</b>	1SDA067061R1
<b>EAN:</b>	8015644007980
<b>Catalog Description:</b>	XT2N 160 Ekip I In=63A 3p F F
<b>Long Description:</b>	C.BREAKER TMAX XT2N 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-I R 63 A

## Ordering

<b>EAN:</b>	8015644007980
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85362090

## Dimensions

<b>Product Net Width:</b>	90 mm
<b>Product Net Height:</b>	130 mm
<b>Product Net Depth:</b>	82.5 mm
<b>Product Net Weight:</b>	1.2 kg

## Container Information

<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	130 mm
<b>Package Level 1 Height:</b>	208 mm
<b>Package Level 1 Length:</b>	145 mm
<b>Package Level 1 Gross Weight:</b>	1.2 kg
<b>Package Level 1 EAN:</b>	8015644007980

## Additional Information

<b>Circuit Breaker Type to be Associated:</b>	Power distribution
<b>Electrical Durability:</b>	120 cycles per hour 8000 cycle
<b>Mechanical Durability:</b>	Nr. Operations 240 cycles per hour Nr. Operations 25000 cycle
<b>Number of Poles:</b>	3
<b>Opening Time:</b>	CB with SOR 15 ms CB with UVR 15 ms

<b>Product Main Type:</b>	SACE Tmax XT
<b>Product Name:</b>	Moulded Case Circuit Breaker
<b>Product Type:</b>	CB
<b>Rated Current (I<sub>n</sub>):</b>	63 A
<b>Rated Frequency (f):</b>	50 / 60 Hz
<b>Rated Voltage (U<sub>r</sub>):</b>	690 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8 kV
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	1000 V
<b>Rated Operational Voltage:</b>	690 V AC
<b>Rated Service Short-Circuit Breaking Capacity (I<sub>cs</sub>):</b>	(220 V AC) 65 kA (220 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (690 V AC) 10 kA
<b>Rated Ultimate Short-Circuit Breaking Capacity (I<sub>cu</sub>):</b>	(220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (690 V AC) 10 kA
<b>Rated Uninterrupted Current (I<sub>u</sub>):</b>	160 A
<b>Release Type:</b>	EL
<b>Standards:</b>	IEC
<b>Sub-type:</b>	XT2
<b>Terminal Connection Type:</b>	Fixed Circuit-Breakers Front
<b>Version:</b>	F

#### Certificates and Declarations (Document Number)

<b>Data Sheet, Technical Information:</b>	1SDC210033D0204
<b>Declaration of Conformity - CE:</b>	9AKK106713A5901
<b>Environmental Information:</b>	1SDL000190R0001
<b>GL Certificate:</b>	1SDL000163R0093
<b>Instructions and Manuals:</b>	1SDH000721R0001
<b>LR Certificate:</b>	1SDL000163R0100

#### Classifications

<b>ETIM 4:</b>	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
----------------	---

**ETIM 5:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

---

**ETIM 6:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.

---

**Object Classification Code:** Q

---

**UNSPSC:** 39120000

