

TM-I
TM-I 18 MM WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com


Process reliability: TM-I

TM-I inlay tags have a guide tab which allows them to slide easily into the transparent sleeves from the type TM. The MultiMark TM-I markers should not be used together with the CLI T sleeves. We currently optimize the usability of the transparent sleeves from the type CLI T. Once the tag is in place, the tab is snapped off at the predetermined break point. The ready-assembled sleeves can then be simply pushed over the conductors. Your benefits: large quantities can be efficiently pre-assembled in a single step.

Your benefits with MultiMark

- Compact, practice-oriented range of products
- Quickly printed and assembled
- Reliable identification of your connections
- Excellent material properties

General ordering data

Type	TM-I 18 MM WS
Order No.	2005470000
Version	TM-I, Insert markers, 18 x 4 mm, White
GTIN (EAN)	4050118390223
Qty.	2,000 pc(s).
compatible printer	2430920000 2448870000 1140490000

Data sheet

TM-I TM-I 18 MM WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	4 mm	Width (inches)	0.157 inch
Height	18 mm	Height (inches)	0.709 inch
Net weight	0.162 g		

General data

Colour	White	Material	Polyester
Number per roll	2,000	Operating temperature range	-40...150 °C
UL 94 flammability rating	HB	Width	4 mm

Conductor and cable markers

Halogen	No
---------	----

Classifications

ETIM 5.0	EC001530	ETIM 6.0	EC001530
eClass 6.2	27-40-04-01	eClass 9.1	27-40-04-01

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD, Zuken E3.S
------------------	--

Data sheet

TM-I
TM-I 18 MM WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

