

**Cutting tools**  
**KT 12**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

**General ordering data**

Type	KT 12
Order No.	<a href="#">9002660000</a>
Version	Cutting tools ,Cutting tool for one-hand operation
GTIN (EAN)	4008190181970
Qty.	1 pc(s).

**Data sheet**

**Cutting tools  
KT 12**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	225 mm	Length (inches)	8.858 inch
Width	63.5 mm	Width (inches)	2.5 inch
Height	30 mm	Height (inches)	1.181 inch
Weight	300 g	Net weight	331.7 g

**Technical data**

Version	One-hand mechanical
---------	---------------------

**Cutting tools**

Copper cable - flexible, max.	35 mm <sup>2</sup>	Copper cable - flexible, max. (AWG)	2
Copper cable - solid, max.	16 mm <sup>2</sup>	Copper cable - solid, max. (AWG)	6
Copper cable - stranded, max.	25 mm <sup>2</sup>	Copper cable - stranded, max. (AWG)	3
Copper cable, max. diameter	12 mm	Data / telephone / control cable, max. Ø	12 mm
Single-core aluminium cable, max.(mm <sup>2</sup> )	25 mm <sup>2</sup>	Stranded aluminium cable, max (mm <sup>2</sup> )	25 mm <sup>2</sup>
Stranded aluminium cable, max. (AWG)	6	Stranded aluminium cable, max. diameter	8 mm

**Classifications**

ETIM 3.0	EC000005	ETIM 4.0	EC000005
ETIM 5.0	EC000142	ETIM 6.0	EC000142
UNSPSC	31-16-31-02	eClass 5.1	27-40-02-01
eClass 6.2	21-04-90-90	eClass 7.1	21-04-90-11
eClass 8.1	21-04-90-11	eClass 9.0	21-04-90-11
eClass 9.1	21-04-37-06		

**Product information**

Descriptive text technical data	Tool closed
---------------------------------	-------------

**Approvals**

Approvals



ROHS	Conform
------	---------