

TM
TM 204/20 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

Type	TM 204/20 V0
Order No.	1806360000
Version	TM, Sleeve x 9 mm, PVC, Colour: Transparent, Conductor O.D.: 6 - 10 mm
GTIN (EAN)	4032248275878
Qty.	500 pc(s).

TM
TM 204/20 V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	9 mm	Width (inches)	0.354 inch
Height	20 mm	Height (inches)	0.787 inch
Depth	9 mm	Depth (inches)	0.354 inch
Net weight	0.716 g		

General data

Colour	Transparent	Material	PVC
Operating temperature range	-40...80 °C	Recommended industries	Transportation, Machinery
Type of printing	blank	UL 94 flammability rating	V-0
Width	9 mm		

Conductor and cable markers

Conductor O.D.	6 - 10 mm	Conductor O.D., max.	10 mm
Conductor O.D., min.	6 mm	Conductor cross-section, max.	16 mm ²
Conductor cross-section, min.	6 mm ²		

Classifications

ETIM 3.0	EC001530	ETIM 4.0	EC001288
ETIM 5.0	EC001288	ETIM 6.0	EC001530
UNSPSC	44-12-17-08	eClass 5.1	27-14-91-03
eClass 6.2	27-14-91-29	eClass 7.1	27-14-91-29
eClass 8.1	27-14-91-03	eClass 9.0	27-14-07-08
eClass 9.1	27-40-04-01		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD, Zuken E3.S
Product change notification	PCN Transparent Sleeves_DE PCN Transparent Sleeves_EN