

Datasheet

Art.No. 70.352.3235.0

Hood BAS GOT GC 32 M32 50 A0

revos BASIC size 32 hood with cable gland M32, top cable entry, double locking lever



| | |
|------------|---------------|
| Art.No. | 70.352.3235.0 |
| EAN | 4015573626560 |
| Order unit | 1 pieces |

Approvals



Technical data

General

| | |
|--|---------------------|
| Housing material | Aluminium |
| Colour | Grey |
| Surface | With powder coating |
| Degree of protection (IP) | IP54 |
| UV resistant | Yes |
| Inflammability class of insulation material acc. with UL94 | Other |
| Operating temperature range min. | -40 °C |
| Operating temperature range max. | 120 °C |

Model

| | |
|------------------------|-----------------------|
| DIN-size | 32 |
| Model | male |
| Locking mechanism | Double locking levers |
| Cable entry | Above |
| Type of cable | Gland nut |
| With cable screw gland | Yes |
| Thread size M | 32 |
| Thread size PG | |
| Hinged lid | No |
| EMC-version | No |
| Length | 94 mm |
| Width | 83 mm |
| Height | 94 mm |

Classification

| | |
|------------|----------|
| ECLASS 8.1 | 27440202 |
| ETIM 6.0 | EC000437 |
| ETIM 5.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 3.0 | EC000437 |

Drawings

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | | | | | | | | | | | | | | |
|---|-------------------------|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|------|---------------|-------------------------|---------------|-------------------------|---------------|-------------------------|---------------|-------------------------|---------------|-------------------------|---------------|-------------------------|
| <p>Top view dimensions: 88.5 (width), 77.5 (height), 67.5 (inner width), 18.5 (inner height), 27 (hole offset), 28 (hole diameter), 8.5 (mounting hole diameter).</p> <p>Side view dimensions: 119 (total height), 94 (height to top of housing), 93.5 (height to top of terminal block).</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Teil-Nr. part no.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Typ</th> <th style="width: 90%;">Type</th> </tr> </thead> <tbody> <tr> <td>70.352.3235.0</td> <td>BAS 60T GC 32 M32 50 A0</td> </tr> <tr> <td>70.352.3235.1</td> <td>BAS 60T GC 32 M32 50 A1</td> </tr> <tr> <td>70.352.3235.2</td> <td>BAS 60T GC 32 M32 50 A2</td> </tr> <tr> <td>70.352.3235.3</td> <td>BAS 60T GC 32 M32 50 A3</td> </tr> <tr> <td>70.352.3235.4</td> <td>BAS 60T GC 32 M32 50 A4</td> </tr> <tr> <td>70.352.3235.5</td> <td>BAS 60T GC 32 M32 50 A5</td> </tr> </tbody> </table> | | | | | | | | | | | | | | | | | | | | | | | | | Typ | Type | 70.352.3235.0 | BAS 60T GC 32 M32 50 A0 | 70.352.3235.1 | BAS 60T GC 32 M32 50 A1 | 70.352.3235.2 | BAS 60T GC 32 M32 50 A2 | 70.352.3235.3 | BAS 60T GC 32 M32 50 A3 | 70.352.3235.4 | BAS 60T GC 32 M32 50 A4 | 70.352.3235.5 | BAS 60T GC 32 M32 50 A5 |
| Typ | Type | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.0 | BAS 60T GC 32 M32 50 A0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.1 | BAS 60T GC 32 M32 50 A1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.2 | BAS 60T GC 32 M32 50 A2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.3 | BAS 60T GC 32 M32 50 A3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.4 | BAS 60T GC 32 M32 50 A4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 70.352.3235.5 | BAS 60T GC 32 M32 50 A5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .0 VERSION .0</p> <p>Kabelverschraubung M32 cable gland M32</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .1 VERSION .1</p> <p>Einsteck M32 thread M32</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .2 VERSION .2</p> <p>Statoren M32 intermediate support with thread M32</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .3 VERSION .3</p> <p>Kabelverschraubung M32 mit Zugentlastung und Biegeschutz cable gland M32 with strain relief and bending protection</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .4 VERSION .4</p> <p>Kabelverschraubung M32 mit Zugentlastung und Biegeschutz cable gland M32 with strain relief and bending protection</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Ausführung .5 VERSION .5</p> <p>Kabelverschraubung M32 cable gland M32</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>GEHÄUSEBEITEIL Housing part</p> <p>Größe: 32 bzw. 48 / M32 von oben size: 32 or rather 48 / M32 TOP 5/16</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Wieland Wieland Electric</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>70.352.3235.01L - 01 D08025 79mm 23272303 08/1402 18.00</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |