

Datasheet

Art.No. 70.340.0635.0

Bottom BAS GUT GR 6 M20 A0

revos BASIC size 6 closed-bottom base with 2 cable glands M20, with cover, single locking lever



Art.No.	70.340.0635.0
EAN	4015573617490
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C




Model

DIN-size	6
Model	Surface mounting (base)
Locking mechanism	Single locking lever
Cable entry	Two-sided
Type of cable	Gland nut
With cable screw gland	Yes
Thread size M	20
Thread size PG	
Hinged lid	Yes
EMC-version	No
Length	84 mm
Width	52 mm
Height	54.7 mm

Classification

ECLASS 8.1	27440202
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437
ETIM 3.0	EC000437


Drawings

Bohrbild
/Cut out

Varianten/Variants

.0



70.340.0635.1	BAS 6UT GR 6 N20 A1	See table below /Threat hole	X
70.340.0635.0	BAS 6UT GR 6 N20 A0	Kabelverschraubung (KV), IP54 montiert /Cable gland (CG), IP54 assembled	
Buchsennummer /Order number	Typ /Type	Varianten /Variants	W- (optional)

Weitere Daten siehe KATALOG oder eKatalog. www.wieland-electric.com
 Additional data see CATALOG or eCatalog. www.eshop.wieland-electric.com

Bohrung für 100 THT/Drilling hole for 100 THT: The drilling hole must be drilled in the center of the terminal block. The diameter of the hole must be 100 THT. The distance between the holes must be 70 mm. The distance between the holes must be 5W/E. The distance between the holes must be Ø5.

Bohrung für 100 THT/Drilling hole for 100 THT: The drilling hole must be drilled in the center of the terminal block. The diameter of the hole must be 100 THT. The distance between the holes must be 70 mm. The distance between the holes must be 5W/E. The distance between the holes must be Ø5.