

Datasheet

Art.No. 71.330.1035.0

Bottom BAS GUT GL 10 M20 A0

revos BASIC size 10 closed-bottom base with 2 cable glands M20, single locking lever



Art.No.	71.330.1035.0
EAN	4015573620841
Order unit	1 pieces

Approvals



Technical data

General

Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	IP54
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	10
Model	Surface mounting (base)
Locking mechanism	Single locking lever
Cable entry	Two-sided
Type of cable	Gland nut
With cable screw gland	Yes
Thread size M	20
Thread size PG	
Hinged lid	No
EMC-version	No
Length	94 mm
Width	52 mm
Height	55 mm

Classification

ECLASS 8.1	27440202
ETIM 6.0	EC000437
ETIM 5.0	EC000437
ETIM 4.0	EC000437
ETIM 3.0	EC000437

Drawings

Bohrbild
/Cut out

71.330.1035.1	BAS GUT 6L 10 M25 A1	Gewindebohrung /Thread hole	X
71.330.1035.0	BAS 6UT 6L 10 M25 A0	Kabelverschraubung (KVV), IP2X montiert /Cable gland (CG), IP2X assembled	
Bestellnummer /Order number		Typ /Type	Ab- /View

Varianten/Variants

.0

Bohrbild
/Cut out

Weitere Daten siehe KATALOG oder eKatalog. www.wieland-electric.com
Additional data see CATALOG or eCatalog. eshop.wieland-electric.com

Dimensions: 10 (1000) / 100 (10000) mm system 500 (5000) mm. The drawing is a technical drawing and does not represent a physical part. The drawing is a technical drawing and does not represent a physical part. The drawing is a technical drawing and does not represent a physical part.