ISO-TP Low Voltage Insulators, Metric Thread - ISOTP40M12 (548511)














- Halogen free
- High resistance to leakage current
- Great stability of electrical and mechanical parameters
- Fiberglass reinforced
- UL® Recognized in E125470 and evaluated for dielectric withstand rating of 1,500 VAC/DC
- RoHS compliant











Part Number	ISOTP40M12
Article Number	548511
Material	Steel Glass Fibre Reinforced Polyamide
Finish	Electrogalvanized
Working Temperature	-40 to 130 °C
Flammability Rating	UL® 94V-0
Complies With	IEC® 60695-2-11 (Glow Wire Test 960 °C)
Dielectric Strength, IEC 61439.1	3,500 VAC @ 1 min
Dielectric Strength, UL	1,500 VAC/DC
Insulation Voltage	1,000 VAC 1,500 VDC
Height (H)	40 mm
Hex Width (W)	46 mm
Depth (D)	53 mm
Thread Size (TS)	M12
Thread Depth (TD)	14.5 mm
Diameter (Ø)	40 mm
Static Load 1 (F1)	11,000 N
Static Load 2 (F2)	4,500 N
Unit Weight	0.102 kg
Certifications	CE CSA-Comp cURus IEC 61439-1 ISO-TP Insulators



Part Number	ISOTP40M12
	RoHS
Standard Packaging Quantity	25 pc
UPC	78285666797
EAN-13	3479775485119

Creepage and clearance distances need to be in accordance with the relevant application standard.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



