

Datasheet

Art.No. Z7.280.3127.0

Insulated jumper bar IVBWK 2,5 -11

Cross connector, insulated for DIN rail terminal blocks type WK ..., 11 -pole



Art.No.	Z7.280.3127.0
EAN	4015573155909
Order unit	10 pieces

Approvals

ATEX

Technical data

General

Colour	Yellow
Type	Cross connector
Modular spacing	5 mm
Number of bridged clamps	11
Mounting method	Screwable
Insulated	Yes

Accessories

Type	Cross connector
Mounting method	Screwable
Insulated	Yes
Colour	Yellow
Number of bridged clamps	11
Modular spacing	5 mm

Classification

ECLASS 8.1	27141140
ETIM 6.0	EC000489
ETIM 5.0	EC000489
ETIM 4.0	EC000489
ETIM 3.0	EC000489

Drawings

1 2 3 4

A

4-polige Ausführung
4 poles variant

Weitere Daten siehe Katalog
further data see catalog

Teile-Nr. part nr.	Pol- zahl poles	L	l	Typ type
Z7.280.2227.0	2	8,9	5	IVB WK 2,5-2
Z7.280.2327.0	3	13,9	10	IVB WK 2,5-3
Z7.280.2427.0	4	18,9	15	IVB WK 2,5-4
Z7.280.2527.0	5	23,9	20	IVB WK 2,5-5
Z7.280.2627.0	6	28,9	25	IVB WK 2,5-6
Z7.280.2727.0	7	33,9	30	IVB WK 2,5-7
Z7.280.2827.0	8	38,9	35	IVB WK 2,5-8
Z7.280.2927.0	9	43,9	40	IVB WK 2,5-9
Z7.280.3027.0	10	48,9	45	IVB WK 2,5-10
Z7.280.3127.0	11	53,9	50	IVB WK 2,5-11
Z7.280.3227.0	12	58,9	55	IVB WK 2,5-12

Information nach DIN 7167/Tolerance system acc. to DIN 7167.
[This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances].

Material: Stahl / Steel

Verwendung: - / First Use: -

Blatt: 1 von 1 / Sheet: 1 of 1

Zeichnung Nr./Drawing No.	Index
Z7.280.2227.0 01K a	a

Maße in mm/Dimensions are in mm

Typ	Bezeichnung/Title
IVB WK 2,5-...	VERBINDUNGSSTEG
	juper bar

04.10.2007/ Datum / Date / Sheet

Änderung/Revision

wieland

Elektrische Verbindungen

Z72802227001K_a_CXW/D42_SchmK_2007-10-01/01/01/02_1/000

QU-PEM-08/91