

General Information

Extended Product Type:	JB12-5
Product ID:	1SNK912305R0000
EAN:	3472599123052
Catalog Description:	JB12-5 Jumper Bar - Orange
Long Description:	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV).

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Ambient Temperature:	-5 ... +40 °C
Color:	Orange
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNK160027C0201
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
EAN:	3472599123052
Flammability According to UL94:	V0
Function:	Jumper Bars
IT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	JB12-5 Jumper Bar - Orange
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Minimum Order Quantity:	20 piece
Object Classification Code:	X
Order Multiple:	20 piece
Package Level 1 EAN:	3472599123052
Package Level 1 Gross Weight:	0.279 kg
Package Level 1 Height:	45 mm
Package Level 1 Length:	105 mm
Package Level 1 Units:	20 piece
Package Level 1 Width:	45 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	200 mm
Package Level 2 Units:	600 piece
Package Level 2 Width:	200 mm
Package Level 3 Units:	9000 piece
Product Main Type:	JB12
Product Name:	Jumper Bar
Product Net Depth:	31.5 mm
Product Net Height:	56 mm
Product Net Weight:	12.0 g

Product Net Weight:	12.9 g
Product Net Width:	12 mm
Product Packing Type:	Box
Rated Current (I_n):	Main Circuit 76 A
Rated Impulse Withstand Voltage (U_{imp}):	6000 V
Rated Voltage (U_r):	1000 V
RoHS Information:	1SND230491F0206
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Spacing:	12 mm
Sub-Function 2:	Screwless
Suitable For:	ZK16 ZK16-3P ZK16-PE ZK16-PE-3P ZS25 ZS25-PE

