

## General Information

<b>Extended Product Type:</b>	JB12-2
<b>Product ID:</b>	1SNK912302R0000
<b>EAN:</b>	3472599123021
<b>Catalog Description:</b>	JB12-2 Jumper Bar - Orange
<b>Long Description:</b>	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV).

## Additional Information

<b>ABB Industrial IT Suite:</b>	Control IT
<b>Ambient Air Temperature:</b>	Operation -55 ... +110 °C Storage -55 ... +110 °C
<b>Ambient Temperature:</b>	-5 ... +40 °C
<b>Color:</b>	Orange
<b>Country of Origin:</b>	France (FR)
<b>Customs Tariff Number:</b>	85369010
<b>Data Sheet, Technical Information:</b>	1SNK160027C0201
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>EAN:</b>	3472599123021
<b>Flammability According to UL94:</b>	V0
<b>Function:</b>	Jumper Bars
<b>IT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SNK160027C0201
<b>Insulation Material:</b>	Polyamide
<b>Invoice Description:</b>	JB12-2 Jumper Bar - Orange
<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>Minimum Order Quantity:</b>	50 piece
<b>Object Classification Code:</b>	X
<b>Order Multiple:</b>	50 piece
<b>Package Level 1 EAN:</b>	3472599123021
<b>Package Level 1 Gross Weight:</b>	0.293 kg
<b>Package Level 1 Height:</b>	45 mm
<b>Package Level 1 Length:</b>	105 mm
<b>Package Level 1 Units:</b>	50 piece
<b>Package Level 1 Width:</b>	45 mm
<b>Package Level 2 Height:</b>	300 mm
<b>Package Level 2 Length:</b>	200 mm
<b>Package Level 2 Units:</b>	1500 piece
<b>Package Level 2 Width:</b>	200 mm
<b>Package Level 3 Units:</b>	96000 piece
<b>Product Main Type:</b>	JB12
<b>Product Name:</b>	Jumper Bar
<b>Product Net Depth:</b>	31.5 mm
<b>Product Net Height:</b>	20 mm
<b>Product Net Weight:</b>	4.0 g

<b>Product Net Weight:</b>	4.9 g
<b>Product Net Width:</b>	12 mm
<b>Product Packing Type:</b>	Box
<b>Rated Current (I<sub>n</sub>):</b>	Main Circuit 76 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6000 V
<b>Rated Voltage (U<sub>r</sub>):</b>	1000 V
<b>RoHS Information:</b>	1SND230491F0206
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
<b>Selling Unit of Measure:</b>	piece
<b>Spacing:</b>	12 mm
<b>Sub-Function 2:</b>	Screwless
<b>Suitable For:</b>	ZK16 ZK16-3P ZK16-PE ZK16-PE-3P ZS25 ZS25-PE

