

## General Information

|                               |   |
|-------------------------------|---|
| <b>Extended Product Type:</b> | BADH  |
| <b>Product ID:</b>            | 1SNA116900R2700   |
| <b>EAN:</b>                   | 3472591169003   |
| <b>Catalog Description:</b>   | BADH End Stops - Grey   |
| <b>Long Description:</b>      | - Give efficient support to the SNA double or triple deck or power terminal blocks assemblies thanks to the BADH double gripping rail contact, - Ease the assemblies identification with SNA markers and label holders. |

## Additional Information

|   |  |
|---|--|
| <b>ABB Industrial IT Suite:</b>           | Control IT   |
| <b>Ambient Air Temperature:</b>           | Operation -55 ... +110 °C<br>Storage -55 ... +110 °C   |
| <b>Ambient Temperature:</b>               | -5 ... +40 °C  |
| <b>Color:</b>                             | Grey   |
| <b>Country of Origin:</b>                 | France (FR)  |
| <b>Customs Tariff Number:</b>             | 85369010   |
| <b>Degree of Protection:</b>              | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20   |
| <b>E-nummer:</b>                          | 4029083  |
| <b>EAN:</b>                               | 3472591169003  |
| <b>ETIM 4:</b>                            | EC001041 - End bracket for terminal block  |
| <b>ETIM 5:</b>                            | EC001041 - End bracket for terminal block  |
| <b>ETIM 6:</b>                            | EC001041 - End bracket for terminal block  |
| <b>Flammability According to UL94:</b>    | V0   |
| <b>Function:</b>                          | End Stops  |
| <b>IIT Publishing Status:</b>             | Level 0 - Information enabled  |
| <b>Industrial IT Certification Level:</b> | 0  |
| <b>Insulation Material:</b>               | Polyamide  |
| <b>Invoice Description:</b>               | BADH End Stops - Grey  |
| <b>Minimum Order Quantity:</b>            | 50 piece   |
| <b>Mounting on DIN Rail:</b>              | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| <b>Object Classification Code:</b>        | X  |
| <b>Order Multiple:</b>                    | 50 piece   |
| <b>Package Level 1 EAN:</b>               | 3472591169003  |
| <b>Package Level 1 Gross Weight:</b>      | 1 kg   |
| <b>Package Level 1 Height:</b>            | 75 mm  |
| <b>Package Level 1 Length:</b>            | 200 mm   |
| <b>Package Level 1 Units:</b>             | 50 piece   |
| <b>Package Level 1 Width:</b>             | 176 mm   |
| <b>Package Level 2 Units:</b>             | 450 piece  |
| <b>Package Level 3 Units:</b>             | 10800 piece  |
| <b>Product Main Type:</b>                 | BADH   |
| <b>Product Name:</b>                      | End Stop   |
| <b>Product Net Depth:</b>                 | 60 mm  |
| <b>Product Net Height:</b>                | 55 mm  |
| <b>Product Net Weight:</b>                | 20 g   |

|                                  |  |
|----------------------------------|--|
| <b>Product Net Width:</b>        | 12 mm  |
| <b>Product Packing Type:</b>     | Box  |
| <b>Recommended Screw Driver:</b> | 5.5 mm   |
| <b>RoHS Date:</b>                | 20160314   |
| <b>RoHS Information:</b>         | 1SND230479F0206  |
| <b>RoHS Status:</b>              | Following EU Directive 2011/65/EC  |
| <b>Selling Unit of Measure:</b>  | piece  |
| <b>Short Description:</b>        | End Stops BADH   |
| <b>Spacing:</b>                  | 12 mm  |
| <b>Suitable For:</b>             | D1.5/6.D2.ADO<br>D1.5/6.D2.ADO.NF<br>D1/5.C4.ADO<br>D1/5.D2.ADO<br>D120/42.AF<br>D120/42.FF<br>D120/42.FF.Ex<br>D150/31.D10<br>D185/55.AF<br>D185/55.FF<br>D185/55.FF.Ex<br>D2.5/5.A.L.L<br>D2.5/5.A.L.L.L<br>D2.5/5.A.L.L.P.L<br>D2.5/5.A.N.L<br>D2.5/5.A.N.L.L<br>D2.5/5.A.N.L.P.L<br>D2.5/5.A.N.T.L.P.L<br>D2.5/5.D2.ADO<br>D2.5/5.D2.L<br>D2.5/5.DD.L<br>D2.5/5.DE.L<br>D2.5/5.DE1.D.L<br>D2.5/5.DE1.L<br>D2.5/5.DE2.D2.L<br>D2.5/5.DE2.L<br>D2.5/5.DL.L<br>D2.5/5.L.L<br>D2.5/5.L.L.L<br>D2.5/5.L.L.P.L<br>D2.5/5.N.L<br>D2.5/5.N.L.L<br>D2.5/5.N.L.P.L<br>D2.5/5.N.T.L.P.L<br>D2.5/5.T1.L<br>D2.5/5.T1.P.L<br>D2.5/5.T3.L<br>D2.5/5.T3.P.L<br>D2.5/6.D<br>D2.5/6.DA<br>D2.5/6.DAL<br>D2.5/6.DL<br>D2.5/6.DP<br>D240/36.D10<br>D300/55.FF<br>D300/55.FF.Ex<br>D35/16.2L<br>D35/16.NT.L<br>D35/16.P.2L<br>D35/27.AF<br>D35/27.FF<br>D35/27.FF.Ex<br>D4/6.A.L.L |

D4/6.A.NLP  
D4/6.A.NTLP  
D4/6.D1.P.ADO  
D4/6.D2.ADO  
D4/6.L  
D4/6.LL  
D4/6.LLP  
D4/6.NL  
D4/6.NLP  
D4/6.NTLP  
D4/6.P.T1  
D4/6.T  
D4/6.T3.P  
D4/8.D2.P.SF  
D6/8.D2.ADO  
D70/22  
D70/22.P  
D70/32.AF  
D70/32.FF  
D70/32.FF.Ex  
D95/26  
D95/26.P  
DBL  
M120/35.AF  
M120/35.F  
M120/35.FF  
M300/42.AF  
M300/42.F  
M300/42.FF  
M35/16.2A.2G  
M35/26.AF  
M35/26.F  
M35/26.FF  
M4/6.D1  
M4/6.D2  
M4/6.D2.2S2  
M4/6.D2.NC  
M4/6.D2.S1R  
M4/6.D2.SB  
M4/6.D2.SNBT  
M4/6.D2.SNBT.NC  
M4/6.DD  
M4/6.DE  
M4/6.DL  
M4/6.DN  
M4/7.D  
M4/8.D2.SF  
M4/8.D2.SF.NC  
M6/8.D  
M6/8.D2.NC  
M70/31.AF  
M70/31.F  
M70/31.FF  
MA2.5/5.D1  
MA2.5/5.D2  
MA2.5/5D-2CPE  
RGW25-M5  
RGW25-M6  
RGW6-R1  
RGW6-ST-1

---

**Tightening Torque:**

acc. IEC 60947-1 1.2 N·m  
Manufacturer 1.4 N·m

