

MO132-10



Products Low Voltage Products and Systems Circuit Breakers Manual Motor Starters

Products Low Voltage Products and Systems Control Products Manual Motor Starters Manual Motor Starters

General Information

Extended Product Type:	MO132-10
Product ID:	1SAM360000R1010
EAN:	4013614400254
Catalog Description:	MO132-10 Manual Motor Starter Magnetic Only
Long Description:	The MO132-10 manual motor starter magnetic only is a compact 45 mm width devices with a rated operational current of $I_e = 10.0$ A. This device is used to manually switch on and off loads/motors and to protect them reliably and without the need for a fuse from short-circuits. The manual motor starter offers a rated service short-circuit breaking capacity $I_{cs} = 50$ kA at 400 VAC. A combination together with overload relays or motor controllers allows the protection of motors. Further features are the build-in disconnect function, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter magnetic only is suitable for three- and single-phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signalling contacts, undervoltage releases, shunt trips, 3-phase bus bars, power in-feed blocks are available as accessory.

Additional Information

ABS Certificate:	1SAA963001-0101
Actuator Type:	Rotary Handle
Ambient Air Temperature:	Around the Enclosure 0 ... +40 °C Operation -25 ... +60 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	No
Ampere Rating UL/CSA:	10 A
BV Certificate:	1SAA963001-0201
CB Certificate:	1SAA963002-2001
CCC Certificate:	1SAA963001-3805
Connecting Capacity Main Circuit UL/CSA:	Flexible 1/2x 16-12 AWG Stranded 1/2x 16-12 AWG
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Contact Position Indication:	ON / OFF / TRIP
Conventional Free-air Thermal Current (I_{th}):	Main Circuit 10 A
Country of Origin:	Germany (DE)
Customs Tariff Number:	85362010
DNV Certificate:	1SAA963001-0302
Data Sheet, Technical Information:	2CDC131035D0201
Data Sheet, Technical Information (Part 2):	1SAM300515F0008
Declaration of Conformity - CE:	1SAD938504-0183
Degree of Protection:	Housing IP20 Main Circuit Terminals IP10
E-number:	3110038
EAC Certificate:	1SAA963000-2701
EAN:	4013614400254
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch

EPLAN Function Definition:	Motor overload switch / Motor overload switch, 6 connection points / Motor overload switch three-pole 1_2_3_4_5_6
ETIM 4:	EC000074 - Motor protective circuit-breaker
ETIM 5:	EC000074 - Motor protective circuit-breaker
ETIM 6:	EC000074 - Motor protection circuit-breaker
Electrical Durability:	50000 cycle
Frequency (f):	0 ... 400 Hz
GL Certificate:	1SAA963001-0401
GOST Certificate:	1SAA963001-2702
General Use Rating UL/CSA:	(600 V AC) 10 A
Horsepower Rating UL/CSA:	(220 ... 240 V AC) Three Phase 3 Hp (440 ... 480 V AC) Three Phase 5 Hp (550 ... 600 V AC) Three Phase 7.5 Hp
Instructions and Manuals:	2CDC131034M6801
Invoice Description:	MO132-10 Manual Motor Starter Magnetic only, 10A
LR Certificate:	1SAA963001-0502
Maximum Operating Altitude Permissible:	2000 m
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Mechanical Durability:	100000 cycle
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 6
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Number of Poles:	3
Number of Protected Poles:	3
Object Classification Code:	F
Package Level 1 EAN:	4013614400254
Package Level 1 Gross Weight:	0.28 kg
Package Level 1 Height:	50 mm
Package Level 1 Length:	95 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	92 mm
Package Level 2 EAN:	4013614443701
Package Level 2 Gross Weight:	11.586 kg
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Units:	40 piece
Package Level 2 Width:	280 mm
Phase Loss Sensitive:	No
Pollution Degree:	3
Power Loss:	at Rated Operating Conditions per Pole 2.2 W
Product Main Type:	MO132
Product Name:	Manual Motor Starter Magnetic Only
Product Net Depth:	86.75 mm
Product Net Height:	90 mm
Product Net Weight:	0.265 kg
Product Net Width:	45 mm
RINA Certificate:	1SAA963000-0802
RMRS Certificate:	1SAA918000-0703
Rated Current (I_n):	10 A

Rated Frequency (f):	Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 6 kV
Rated Instantaneous Short-Circuit Current Setting (I_i):	125 A
Rated Insulation Voltage (U_i):	690 V
Rated Operational Current (I_e):	10 A
Rated Operational Current AC-3 (I_e):	10 A
Rated Operational Power AC-3 (P_e):	(400 V) Three Phase 4 kW
Rated Operational Voltage:	Main Circuit 690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(230 V AC) 50 kA (400 V AC) 50 kA (440 V AC) 20 kA (500 V AC) 20 kA (690 V AC) 3 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(230 V AC) 50 kA (400 V AC) 50 kA (440 V AC) 20 kA (500 V AC) 20 kA (690 V AC) 3 kA
Rated Uninterrupted Current (I_u):	10 A
Recommended Screw Driver:	Pozidriv 2
Remarks:	For overload protection of the motors, an appropriate thermal or electronic overload relays must be used
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6:	5g / 3 ... 150 Hz
RoHS Date:	0159
RoHS Information:	1SAA963002-4405
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selectivity Category:	A
Selling Unit of Measure:	piece
Setting Range:	None
Short Description:	MO132-10 Manual Motor Starter
Short-Circuit Protective Devices:	gG Type Fuses 100 A, 440 V AC gG Type Fuses 100 A, 500 V AC
Standards:	IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Suitable for Isolation:	Yes
Terminal Type:	Screw Terminals
Tightening Torque:	Main Circuit 0.8 ... 1.2 N·m
Tightening Torque UL/CSA:	Main Circuit 10 in·lb
Trip Class:	None
UL Certificate:	UL_E137861 UL_E345003
UNSPSC:	39121521
Utilization:	Starter Protection
Wire Stripping Length:	Main Circuit 9 mm
cUL Certificate:	cUL_E137861

cUL_E345003

cULus Certificate:

cUL_E137861

eClass:

7.0 27370401
