


## “TWIN” POLYPROPYLENE INSULATED END SLEEVES

for fine stranded cables

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	nd#4, HNKE16 and HNKE 50	Quantity Bag
		C	B	P	L			
2 x 0,5	PKET 508	4,6x2,6	1,5	8,0	15,0	○ white	1	500
2 x 0,75	PKET 7508	5,2x2,6	2,1	8,0	15,0	● blue	1,5	500
	PKET 7512	5,2x2,6	2,1	12,0	19,0			500
2 x 1	PKET 108	5,8x3,2	2,6	8,0	16,0	● red	2,5	500
	PKET 112	5,8x3,2	2,6	12,0	20,0			500
2 x 1,5	PKET 1508	6,5x3,6	2,6	8,0	16,0	● black	2,5	500
	PKET 1512	6,5x3,6	2,6	12,0	20,0		2,4	500
2 x 2,5	PKET 2510	7,5x4,3	3,2	10,0	18,0	○ grey	4	250
	PKET 2512	7,5x4,3	3,2	12,0	21,0			250
2 x 4	PKET 412	9,0x5,2	4,2	12,0	23,0	● orange	6	100
2 x 6	PKET 614	10,0x7,2	5,3	14,0	26,0	● green	10	100
2 x 10	PKET 1014	13,0x7,2	7,0	14,0	26,0	● brown	16	100
2 x 16	PKET 1616	18,0x9,5	8,8	16,0	30,0	○ white	35	100

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	nd#4, HNKE16 and HNKE 50	Quantity Bag
		C	B	P	L			
2 x 0,5	PKCT 508	4,6x2,6	1,5	8,0	15,0	● orange	1	500
2 x 0,75	PKCT 7508	5,2x2,6	2,1	8,0	15,0	○ white	1,5	500
	PKCT 7512	5,2x2,6	2,1	12,0	19,0			500
2 x 1	PKCT 108	5,8x3,2	2,6	8,0	16,0	● yellow	2,5	500
	PKCT 112	5,8x3,2	2,6	12,0	20,0			500
2 x 1,5	PKCT 1508	6,5x3,6	2,6	8,0	16,0	● red	2,5	500
	PKCT 1512	6,5x3,6	2,6	12,0	20,0		2,4	500
2 x 2,5	PKCT 2510	7,5x4,3	3,2	10,0	18,0	● blue	4	250
	PKCT 2512	7,5x4,3	3,2	12,0	21,0			250
2 x 4	PKCT 412	9,0x5,2	4,2	12,0	23,0	○ grey	6	100
2 x 6	PKCT 614	10,0x7,2	5,3	14,0	26,0	● black	10	100
2 x 10	PKCT 1014	13,0x7,2	7,0	14,0	26,0	○ ivory	16	100
2 x 16	PKCT 1616	18,0x9,5	8,8	16,0	30,0	● green	35	100



## UNINSULATED END SLEEVES

for flexible Copper cables

Conductor Size sqmm	Ref.	Dimensions mm			Quantity Box/Bag
		Ø	L	C	
0,5	*KE 506 ST	1,0	6,0	1,9	50.000/500
	KE 508 ST	1,0	8,0	1,9	50.000/500
0,75	*KE 7506 ST	1,2	6,0	2,2	40.000/500
	KE 7508 ST	1,2	8,0	2,2	50.000/500
1	*KE 106 ST	1,4	6,0	2,4	25.000/500
	*KE 110 ST	1,4	10,0	2,4	25.000/500
1,5	KE 1508 ST	1,7	8,0	2,8	25.000/500
	*KE 1510 ST	1,7	10,0	2,8	25.000/500
2,5	KE 2508 ST	2,2	8,0	3,4	25.000/500
	*KE 2510 ST	2,2	10,0	3,4	15.000/500
4	KE 410 ST	2,8	10,0	4,0	12.500/500
	*KE 412 ST	2,8	12,0	4,0	10.000/500
6	*KE 610 ST	3,5	10,0	4,7	10.000/500
	*KE 612 ST	3,5	12,0	4,7	7.500/500
10	*KE 616 ST	3,5	15,0	4,7	5.000/500
	*KE 1016 ST	4,5	15,0	5,8	4.000/250
16	*KE 1616 ST	5,8	15,0	7,5	3.000/250
	KE 25015 ST	7,3	15,0	9,5	1.500/100
25	*KE 25018 ST	7,3	18,0	9,5	1.500/100
	KE 35012 ST	8,3	12,0	10,5	1.500/100
35	KE 35015 ST	8,3	16,0	10,5	1.500/100
	*KE 35018 ST	8,3	18,0	10,5	1.000/100

\*To DIN standard 46 228/1

# PKET PKCT



Type PKET, PKCT ranges of twin end sleeves are manufactured from Tin plated electrolytic Copper.

Designed to accommodate two cables terminating in the same sleeve they are ideal for looping conductors.

The operating temperature range is - 20 to + 105°C (Surge + 110°C).

Recommended crimping tools are shown on pages 98 to 121, 125, 152, 154, 156.

# KE



KE series end sleeves are manufactured from Tin plated electrolytic Copper.

Designed and developed for use with flexible cables.

Recommended crimping tools are shown on pages 98 to 121, 125, 152, 154, 156.