

POLYPROPYLENE INSULATED END SLEEVES

for flexible Copper cables

**PKE
PKC
CPKD**



The PKE, PKC, CPKD range of end sleeves is manufactured from Tin plated electrolytic Copper. Designed and developed to reinforce fine wire strands when terminating a cable into a connector block.

The operating temperature range is - 20 to + 105°C (Surge + 110°C).

Recommended crimping tools are shown on pages 98 to 122, 125, 152, 154, 156.

VALSTAR ND#2/PKE

Comprising:

- a selection of PKE end sleeves conductor size 1÷6 sqmm
- tool ND#2


VALSTAR ND#2/PKC

Comprising:

- a selection of PKC end sleeves conductor size 1÷6 sqmm
- tool ND#2



HALOGEN FREE



Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKE 308	1,9	1,1	8,0	12,4	● yellow	25.000/500
0,3÷0,5	PKE 508	2,6	1,3	8,0	14,0	○ white	10.000/500
0,75	PKE 7508	3,4	1,6	8,2	14,6	● blue	10.000/500
1,0	PKE 108	3,4	1,8	8,2	14,6	● red	10.000/500
1,5	PKE 1508	3,8	2,1	8,2	14,6	● black	5.000/500
	PKE 1518	3,8	2,1	18,0	24,4		
2,5	PKE 2508	4,4	2,6	8,2	15,2	○ grey	7.500/500
	PKE 2518	4,4	2,6	18,0	25,0		
4,0	PKE 409	4,8	3,2	9,0	16,0	● orange	5.000/200
	PKE 418	4,8	3,2	18,0	25,0		
6,0	PKE 612	5,8	3,9	12,0	20,0	● green	2.500/100
	PKE 618	5,8	3,9	18,0	26,0		
10,0	PKE 1012	7,4	4,8	12,0	21,5	● brown	1.500/100
	PKE 1018	7,4	4,8	18,0	27,5		
16,0	PKE 1612	9,3	5,9	12,0	22,7	○ white	1.000/100
	PKE 1618	9,3	5,9	18,0	28,6		
25,0	PKE 25016	10,0	7,9	16,0	29,0	● black	500/50
	PKE 25022	10,0	7,9	22,0	35,0		

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKC 306	1,9	1,1	6,0	10,4	● light blue	25.000/500
	PKC 308	1,9	1,1	8,0	12,4		
0,3÷0,5	PKC 508	2,6	1,3	8,0	14,0	● orange	10.000/500
	PKC 510	2,6	1,3	10,0	16,0		
0,75	PKC 7508	3,4	1,6	8,2	14,6	○ white	10.000/500
	PKC 7512	3,4	1,6	12,0	18,4		
1,0	PKC 108	3,4	1,8	8,2	14,6	● yellow	10.000/500
	PKC 112	3,4	1,8	12,0	18,4		
1,5	PKC 1508	3,8	2,1	8,2	14,6	● red	10.000/500
	PKC 1518	3,8	2,1	18,0	24,4		
2,5	PKC 2508	3,9	2,6	8,2	15,2	● blue	7.500/500
	PKC 2518	3,9	2,6	18,0	25,0		
4,0	PKC 409	4,8	3,2	9,0	16,0	○ grey	5.000/200
	PKC 418	4,8	3,2	18,0	25,0		
6,0	PKC 612	5,8	3,9	12,0	20,0	● black	2.500/100
	PKC 618	5,8	3,9	18,0	26,0		
10,0	PKC 1012	7,4	4,8	12,0	21,5	○ ivory	1.500/100
	PKC 1018	7,4	4,8	18,0	27,5		
16,0	PKC 1612	9,3	5,9	12,0	22,7	● green	1.000/100
	PKC 1618	9,3	5,9	18,0	28,6		
25,0	PKC 25016	10,0	7,9	16,0	29,0	● brown	500/50
	PKC 25022	10,0	7,9	22,0	35,0		
35,0	PKC 35016	12,0	8,9	16,0	30,0	● beige	500/50
	PKC 35025	12,0	8,9	25,0	39,0		
50,0	PKC 50020	13,8	11,0	20,0	36,0	● olive	300/50
	PKC 50030	13,8	11,0	30,0	46,0		
70	PKC 70022	16,0	14,3	22,0	38,0	● yellow	100/25
95	PKC 95025	18,0	15,7	25,0	44,0	● red	100/25
120	PKC 120027	21,0	17,5	27,0	48,0	● blue	100/25

Insulated chain end sleeves

Developed for use with production equipment to give a quick and reliable crimped joint. Conforms to DIN standard 46 228/4.

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Reel
		Ø	B	P	L		
0,3÷0,5	CPKD 508	2,6	1,3	8,0	14,0	○ white	5.000
0,75	CPKD 7508	2,8	1,5	8,0	14,0	○ grey	5.000
1	CPKD 108	3,0	1,7	8,0	14,0	● red	5.000
1,5	CPKD 1508	3,5	2,0	8,0	14,0	● black	5.000
2,5	CPKD 2508	4,2	2,5	8,0	14,0	● blue	3.000

HALOGEN FREE

