

RF-F
BF-F
GF-F











Manufactured from Brass strip
- Electrolytically Tin plated
- The operating temperature range is -20 to +115°C (Surge +130°C).
- Recommended crimping tools are shown on pages 98 to 117, 152

FEMALE DISCONNECT TERMINALS









Certified according to
EN 45545-2:2013



Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-F 305	2,8 x 0,5	3.000/100
	 RF-F 308♦	2,8 x 0,8	3.000/100
	 RF-F 405	4,8 x 0,5	2.500/100
	 RF-F 408	4,8 x 0,8	2.500/100
1,5÷2,5 (16÷14)	 BF-F 608	6,35 x 0,8	2.000/100
	 BF-F 405	4,8 x 0,5	2.500/100
	 BF-F 408	4,8 x 0,8	2.500/100
4÷6 (12÷10)	 GF-F 608	6,35 x 0,8	1.000/100

Polycarbonate fully insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-F 305P	2,8 x 0,5	2.000/100
	 RF-F 308P♦	2,8 x 0,8	2.000/100
	 RF-F 405P	4,8 x 0,5	1.500/100
	 RF-F 408P	4,8 x 0,8	1.500/100
1,5÷2,5 (16÷14)	 BF-F 608P	6,35 x 0,8	1.000/100
	 BF-F 405P	4,8 x 0,5	1.500/100
	 BF-F 408P	4,8 x 0,8	1.500/100
4÷6 (12÷10)	 GF-F 608P	6,35 x 0,8	800/100

♦ Not UL approved

RF-M
BF-M
GF-M






Manufactured from Brass strip
- Electrolytically Tin plated
- The operating temperature range is -20 to +115°C (Surge +130°C).
- Recommended crimping tools are shown on pages 98 to 117, 152

MALE DISCONNECT TERMINALS



Certified according to
EN 45545-2:2013



Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-M 608	6,35 x 0,8	3.000/100
1,5÷2,5 (16÷14)	 BF-M 608	6,35 x 0,8	2.000/100
4÷6 (12÷10)	 GF-M 608	6,35 x 0,8	1.000/100

Polycarbonate fully insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-M 608P	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	 BF-M 608P	6,35 x 0,8	1.000/100

RF-FM
BF-FM
RF-B BF-B





Manufactured from Brass strip
- Electrolytically Tin plated
- The operating temperature range is -20 to +115°C (Surge +130°C).
- Recommended crimping tools are shown on pages 98 to 117, 152

MALE/FEMALE CONNECTORS

Certified according to
EN 45545-2:2013







Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-FM 608	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	 BF-FM 608	6,35 x 0,8	1.000/100

BULLET AND SOCKET CONNECTORS

Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Ø mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	 RF-BM 4♦	4	2.500/100
	 RF-BF 4♦	4	800/100
1,5÷2,5 (16÷14)	 BF-BM 5♦	5	2.000/100
	 BF-BF 5♦	5	800/100

♦ Not UL approved