



Main

| | |
|-----------------------------|---|
| Range | Spacial |
| Product name | Spacial S3D |
| Device application | Multi-purpose |
| Product or component-type | Compact enclosure |
| Enclosure nominal-height | 1200 mm |
| Enclosure nominal width | 1000 mm |
| Enclosure nominal depth | 400 mm |
| Door type | Plain |
| Mounting plate description | Plain |
| Type of gland plate | Standard |
| Installation accessory-type | Wall-mounting |
| Device composition | Body 1 Cable gland plate 2 Door with lock 2 Mounting plate 1 |

Complementary

| | |
|-----------------------------|---|
| Variant particularity | Gutter-shaped front rail double sheet thickness Single piece body |
| Number of doors | 2 front face |
| Door opening side | Reversible 120 ° |
| Lock type | 3 points lock, 3 mm double-bar |
| Accessibility for operation | Front |
| Removable parts | Door by hinges Cable gland plate by screws Mounting plate by fixing element |
| Material | Galvanised steel for mounting plate Steel for enclosure |
| Surface finish | Epoxy-polyester powder enclosure |
| Colour | Grey RAL 7035 enclosure : |
| Standards | IEC 62208 |
| Product certifications | CUL LR DNV BV GL UL |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Product Life Status : **Commercialised**