# Product data sheet Characteristics

## **NSYS3X4620**

SPACIAL S3X stainless 304L, Scotch Brite® finish, H400xW600xD200 mm.





#### Main

| Range                        | Spacial                             |
|------------------------------|-------------------------------------|
| Product name                 | Spacial S3X                         |
| Device application           | Multi-purpose                       |
| Product or component-type    | Compact enclosure                   |
| Enclosure nominal-<br>height | 400 mm                              |
| Enclosure nominal width      | 600 mm                              |
| Enclosure nomi-<br>nal depth | 200 mm                              |
| Installation accessory-type  | Wall-mounting                       |
| Device composition           | 1 body<br>1 door<br>1 lock ( door ) |
|                              |                                     |

#### Complementary

| Body type                   | Single piece body, cross-shaped structure<br>Gutter shaped front rail           |  |
|-----------------------------|---|--|
| Door type                   | Plain   |  |
| Number of doors             | Front face : 1 door(s)  |  |
| Door opening side           | 120 °, reversible   |  |
| Lock type                   | 3 mm double-bar lock  |  |
| Mounting plate description  | Without mounting plate  |  |
| Type of gland plate         | Without gland plate   |  |
| Accessibility for operation | Front   |  |
| Removable parts             | Door fixing: by hinges  |  |
| Material                    | Lock : zamak<br>Hinge : stainless steel<br>Body and door : stainless steel 304L |  |
| Surface finish              | Lock : chromium plated Body and door : Scotch-Brite® brushed                    |  |
| Thickness                   | 1.5 mm  |  |

#### **Environment**

| Standards                    | IEC 62208                     |  |
|------------------------------|-------------------------------|--|
| Product certifications       | UL 508 type A<br>CAN/CSA 22   |  |
| IP degree of protection      | IP66 conforming to IEC 60529  |  |
| IK degree of protection      | IK10 conforming to IEC 62262  |  |
| Environmental characteristic | Corrosive<br>Specific hygiene |  |
|                              |                               |  |

## Offer Sustainability

| Sustainable offer status         | Green Premium product  |
|----------------------------------|--|
| RoHS (date code: YYWW)           | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACh                            | Reference not containing SVHC above the threshold  |
| Product environmental profile    | Available Product Environmental  |
| Product end of life instructions | Need no specific recycling operations  |

### Contractual warranty

Product Life Status : Commercialised

