Product data sheet Characteristics

NSYSMWFIX

Spacial SM wall mounting fixing support - set of 2





Main

| Range | Spacial |
|---|---------------------|
| Accessory / sepa- rate part category | Fixing accessory |
| Product or component-type | Wall fixing support |
| Device application | Multi-purpose |
| Enclosure nomi- nal dimensions | - |
| Mounting location | Rear of enclosure |
| Range compatibility | Spacial SM |
| Device composition | 2 x support |
| Quantity per set | Set of 1 |
| | |

Complementary

| Material | Steel |
|----------------------------|------------------------------|
| Surface finish | Zinc coated |
| Fixing mode | By screws - outside location |
| Permanent permissible load | 0 kg |
| Height | 30 mm |
| Width | 170 mm |
| Depth | 110 mm |

Offer Sustainability

| Sustainable offer status | Green Premium product | | | |
|----------------------------------|--|--|--|--|
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity | | | |
| REACh | Reference not containing SVHC above the threshold | | | |
| Product environmental profile | Available | | | |
| Product end of life instructions | Need no specific recycling operations | | | |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|
| | | |

| Product Li | fe Status: (| С. | C | n | ٦r | ne | ı | cia | al | lise | 20 | 1 |
|-------------|--------------|------|---|-----|----|-----|----|-----|----|------|----|---|
| I IUUUUL LI | ie olalus . | ${}$ | · | " 1 | | יוו | 71 | OIC | aı | 131 | - | |