

AF265-40-11-11



Products → Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

General Information

Extended Product Type:	AF265-40-11-11
Product ID:	1SFL547102R1111
EAN:	7320500505502
Catalog Description:	AF265-40-11-11 Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V. Operated with wide control voltage range 24-60 V, 50 and 60 Hz, 20-60 V DC

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	184,4 mm
Product Net Depth / Length:	180 mm
Product Net Height:	225,4 mm
Product Net Weight:	5.55 kg

Technical

Number of Main Contacts NO:	4
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 400 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 400 A (1000 V) 40 °C 350 A (690 V) 70 °C 290 A (690 V) 60 °C 350 A (1000 V) 60 °C 300 A (1000 V) 70 °C 240 A
Rated Operational Current AC-3 (I_e):	(415 V) 55 °C 265 A (220 / 230 / 240 V) 55 °C 265 A (440 V) 55 °C 265 A (380 / 400 V) 55 °C 265 A

Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 75 kW (380 / 400 V) 132 kW (440 V) 160 kW (415 V) 132 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1:	8 x I _e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1:	10 x I _e AC-3
Short-Circuit Protective Devices:	gG Type Fuses 630 A
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1224 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2120 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 2650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 865 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 3800 A
Maximum Electrical Switching Frequency:	AC-1 300 cycles per hour
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Mechanical Durability:	5 million
Maximum Mechanical Switching Frequency:	300 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 x U _c Min. ... 1.1 x U _c Max. (at θ ≤ 70 °C) °C
Rated Control Circuit Voltage (U_c):	60 Hz 24 ... 60 V 50 Hz 24 ... 60 V DC Operation 20 ... 60 V
Coil Consumption:	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 475 V·A Holding at Max. Rated Control Circuit Voltage DC 3 W Holding at Max. Rated Control Circuit Voltage 50 Hz 8.5 V·A Pull-in at Max. Rated Control Circuit Voltage DC 400 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 475 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 8.5 V·A
Operate Time:	Between Coil De-energization and NO Contact Opening 45 ... 80 ms Between Coil Energization and NO Contact Closing 30 ... 60 ms
Connecting Capacity Main Circuit:	Rigid Al-Cable 1 x 185 ... 240 mm ² Rigid Cu-Cable 2 x 70 ... 185 mm ² Flexible 2 x 70 ... 185 mm ²
Connecting Capacity Auxiliary Circuit:	Solid 2 x 1 ... 4 mm ² Flexible with Insulated Ferrule 1 x 0.75 ... 2.5 mm ² Stranded 2 x 1 ... 4 mm ² Flexible 2x0.75 ... 2.5 mm ² Flexible with Ferrule 2 x 0.75 ... 2.5 mm ²

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
------------------------------	--

Terminal Type:	Main Circuit: Bars
-----------------------	--------------------

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... +50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +70 °C Close to Contactor for Storage -40 ... +70 °C
---------------------------------	---

Maximum Operating Altitude Permissible:	3000 m
--	--------

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
--	--------------------

General Use Rating UL/CSA:	(600 V AC) 300 A
-----------------------------------	------------------

Certificates and Declarations (Document Number)

CB Certificate:	SEMKO_SE-73326
------------------------	----------------

CCC Certificate:	CQC_2014010304676670
-------------------------	----------------------

cUL Certificate:	20140910-E73397
-------------------------	-----------------

DNV GL Certificate:	DNV_E-14043
----------------------------	-------------

LR Certificate:	LR_14_70011(E1)
------------------------	-----------------

Container Information

Package Level 1 Units:	1 piece
-------------------------------	---------

Package Level 1 Gross Weight:	6.38 kg
--------------------------------------	---------

Package Level 1 EAN:	7320500505502
-----------------------------	---------------

Classifications

Object Classification Code:	Q
------------------------------------	---

E-nummer:	3210338
------------------	---------

ETIM 4:	EC000066 - Magnet contactor, AC-switching
----------------	---

ETIM 5:	EC000066 - Magnet contactor, AC-switching
----------------	---

ETIM 6:	EC000066 - Power contactor, AC switching
----------------	--

