



Main

| | |
|---------------------------|---------------------------------|
| Range of product | TeSys K |
| Range | TeSys |
| Product or component type | Contacteur |
| Product name | TeSys K |
| Device short name | LC1K |
| Contacteur application | Motor control Resistive load |

Complementary

| | |
|--|--|
| Utilisation category | AC-3 AC-4 AC-1 |
| Poles description | 3P |
| Pole contact composition | 3 NO |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz for power circuit <= 690 V AC 50/60 Hz for signalling circuit |
| [Ie] rated operational current | 20 A (<= 50 °C) at <= 440 V AC AC-1 for power circuit 16 A (<= 70 °C) at 690 V AC AC-1 for power circuit 12 A at <= 440 V AC AC-3 for power circuit |
| Control circuit type | AC 50/60 Hz |
| Control circuit voltage | 230...240 V AC 50/60 Hz |
| Motor power kW | 4 kW at 480 V AC 50/60 Hz 4 kW at 500...600 V AC 50/60 Hz 4 kW at 660...690 V AC 50/60 Hz 5.5 kW at 380...415 V AC 50/60 Hz 5.5 kW at 440 V AC 50/60 Hz 3 kW at 220...230 V AC 50/60 Hz |
| Auxiliary contact composition | 1 NC |
| [Uimp] rated impulse withstand voltage | 8 kV |
| Overvoltage category | III |

| | |
|--|--|
| [I _{th}] conventional free air thermal current | 10 A at ≤ 50 °C for signalling circuit 20 A at ≤ 50 °C for power circuit |
| I _{rms} rated making capacity | 110 A AC for signalling circuit conforming to IEC 60947 144 A AC for power circuit conforming to IEC 60947 144 A AC for power circuit conforming to NF C 63-110 |
| Rated breaking capacity | 80 A at 500 V conforming to IEC 60947 70 A at 660...690 V conforming to IEC 60947 110 A at 440 V conforming to IEC 60947 |
| [I _{lcw}] rated short-time withstand current | 55 A ≤ 50 °C 1 min power circuit 80 A 1 s signalling circuit 75 A ≤ 50 °C 30 s power circuit 100 A ≤ 50 °C 10 s power circuit 90 A 500 ms signalling circuit 25 A ≤ 50 °C ≥ 15 s power circuit 115 A ≤ 50 °C 1 s power circuit 50 A ≤ 50 °C 3 min power circuit 110 A 100 ms signalling circuit 105 A ≤ 50 °C 5 s power circuit |
| Associated fuse rating | 25 A gG at ≤ 440 V for power circuit 10 A gG for signalling circuit conforming to IEC 60947 10 A gG for signalling circuit conforming to VDE 0660 25 A aM for power circuit |
| Average impedance | 3 mΩ at 50 Hz - I _{th} 20 A for power circuit |
| [U _i] rated insulation voltage | 690 V for signalling circuit conforming to IEC 60947-4-1 600 V for signalling circuit conforming to CSA C22.2 No 14 600 V for signalling circuit conforming to UL 508 690 V for signalling circuit conforming to IEC 60947-5-1 600 V for power circuit conforming to CSA C22.2 No 14 600 V for power circuit conforming to UL 508 690 V for power circuit conforming to IEC 60947-4-1 |
| Insulation resistance | > 10 MΩ for signalling circuit |
| Inrush power in VA | 30 VA at 20 °C |
| Hold-in power consumption in VA | 4.5 VA at 20 °C |
| Heat dissipation | 1.3 W |
| Control circuit voltage limits | 0.2...0.75 U _c at ≤ 50 °C drop-out 0.8...1.15 U _c at ≤ 50 °C operational |
| Connections - terminals | Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 0.75...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 0.75...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 0.34...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 2 cable(s) 1.5...4 mm ² - cable stiffness: solid |
| Operating rate | 3600 cyc/h |
| Auxiliary contacts type | Type instantaneous (1 NC) |
| Signalling circuit frequency | ≤ 400 Hz |
| Minimum switching current | 5 mA for signalling circuit |
| Minimum switching voltage | 17 V for signalling circuit |
| Mounting support | Rail Plate |
| Tightening torque | 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 |
| Operating time | 10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Non overlap distance | 0.5 mm |
| Mechanical durability | 10 Mcycles |
| Electrical durability | 1.3 Mcycles 12 A AC-3 at U _e ≤ 440 V 0.3 Mcycles 20 A AC-1 at U _e ≤ 440 V |
| Mechanical robustness | Shocks contactor closed, on Y axis 15 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on X axis 6 Gn for 11 ms IEC 60068-2-27 Shocks contactor opened, on Z axis 10 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on Z axis 15 Gn for 11 ms IEC 60068-2-27 Shocks contactor closed, on X axis 10 Gn for 11 ms IEC 60068-2-27 Vibrations contactor closed 4 Gn, 5...300 Hz IEC 60068-2-6 |

Shocks contactor opened, on Y axis 10 Gn for 11 ms IEC 60068-2-27
Vibrations contactor opened 2 Gn, 5...300 Hz IEC 60068-2-6

| | |
|--------------------|---------|
| Height | 58 mm |
| Width | 45 mm |
| Depth | 57 mm |
| Product weight | 0.18 kg |
| Compatibility code | LC1K |

Environment

| | |
|---------------------------------------|--|
| Standards | NF C 63-110 VDE 0660 BS 5424 IEC 60947 |
| Product certifications | UL CSA |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Protective treatment | TC conforming to IEC 60068 TC conforming to DIN 50016 |
| Ambient air temperature for operation | -25...50 °C |
| Ambient air temperature for storage | -50...80 °C |
| Operating altitude | 2000 m without derating in temperature |
| Flame retardance | Requirement 2 conforming to NF F 16-102 V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0640 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available End of life manual |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|