



Main

| | |
|---------------------------|-------------------|
| Range of product | TeSys K |
| Range | TeSys |
| Device short name | LA4K |
| Product or component type | Suppressor module |
| Product compatibility | LC1 LP1 |

Complementary

| | |
|-------------------------|----------------|
| Mounting location | Front side |
| Mounting mode | Clip-on |
| Suppressor technology | RC circuit |
| Control circuit voltage | 110...250 V AC |
| Maximum peak voltage | 3 Uc |
| Local signalling | LED |
| Quantity per set | Set of 5 |
| Height | 25 mm |
| Width | 6 mm |
| Depth | 22 mm |
| Product weight | 0.01 kg |
| Compatibility code | LA4K |

Environment

| | |
|------------------------|---|
| Standards | NF C 63-110 BS 5424 VDE 0660 IEC 60947 |
| Product certifications | UL CSA |

| | |
|---------------------------------------|--|
| IP degree of protection | IP2x conforming to VDE 0106 |
| Protective treatment | TC conforming to IEC 60068 TC conforming to DIN 50016 |
| Ambient air temperature for operation | -25...50 °C |
| Ambient air temperature for storage | -50...80 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|