



Main

Range of product	TeSys F
Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FJ
Range compatibility	TeSys F LC1F contactor
Control circuit type	AC 40...400 Hz
Control circuit voltage	415...440 V AC 40...400 Hz
Average resistance	145 Ohm inrush at 20 °C 4070 Ohm holding at 20 °C
Inductance of closed circuit	19.4 H
Product compatibility	LC1F400
Operating time	100...170 ms opening 40...75 ms closing
Mechanical durability	10 Mcycles
Operating rate	2400 cyc/h at <= 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.85...1.1 Uc at 55 °C operational 40...400 Hz 0.3...0.5 Uc at 55 °C drop-out 40...400 Hz
Inrush power in VA	1075 VA at 20 °C (cos f 0.9) 40...400 Hz
Hold-in power consumption in VA	15 VA at 20 °C (cos f 0.3) 40...400 Hz
Heat dissipation	14 W at 40...400 Hz

Environment

Ambient air temperature for operation	> -5...55 °C
Product weight	1 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty period	18 months
-----------------	-----------
