Product datasheet Characteristics

GV1G09

TeSys GV2, TeSys D & TeSys U - terminal block - 3P - from the top



Main

IVIAIII		
Range of product	TeSys GV2	
	TeSys D	
	TeSys U	
	TeSys K	
Range	Linergy	
Product name	FT	
Device short name	GV1G	
Product or component type	Terminal block	
Accessory / separate part category	Connection accessory	
Poles description	3P	
Range compatibility	TeSys - K	
	TeSys - LS1	
	TeSys - D	
	TeSys - GV2	
	TeSys - U	

Complementary

[le] rated operational current	63 A	
Mounting location	Тор	
IP degree of protection	IP20 according to IEC 60529	
[Ui] rated insulation voltage	690 V according to IEC 60947-1	, a
Connections - terminals	Screw clamp terminals 1 cable(s) 1.510 mm² flexible with Screw clamp terminals 2 cable(s) 1.52 mm² flexible with Screw clamp terminals 1 solid AWG 4 Screw clamp terminals 1 flexible AWG 4 Screw clamp terminals 2 cable(s) 1.56 mm² solid Screw clamp terminals 2 cable(s) 2.54 mm² flexible without Screw clamp terminals 1 cable(s) 1.516 mm² flexible without Screw clamp terminals 1 cable(s) 1.525 mm² solid	documentation is not intended
Tightening torque	1.7 N.m - on screw clamp terminals 2.2 N.m - on connector	ес. ————————————————————————————————————
Product weight	0.04 kg	<u> </u>

Compatibility code	GV1G	
Contractual warranty		
Warranty period	18 months	

