

General Information

Extended Product Type:	AF116-30-11-13
Product ID:	1SFL427001R1311
EAN:	7320500476376
Catalog Description:	AF116-30-11-13 Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 690 V. Operated with wide control voltage range 100-250 V, 50/60 Hz and DC

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40...+70 °C Close to Contactor for Storage -40...+70 °C
Battery Information:	Type NONE
Block Contactor Type:	3-Pole Contactor
CB Certificate:	SE-70479
CCC Certificate:	CQC_2013010304604055
Coil Consumption:	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 130 V·A Holding at Max. Rated Control Circuit Voltage DC 3 W Holding at Max. Rated Control Circuit Voltage 50 Hz 6 V·A Pull-in at Max. Rated Control Circuit Voltage DC 135 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 130 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 6 V·A
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 x Uc Min. ... 1.1 x Uc Max. (at $\theta \leq 70$ °C) °C
Coil Voltage Code:	13
Connecting Capacity:	Flexible 2x10...70 mm ² Rigid Cu-Cable 2x10...95 mm ²
Connecting Capacity Auxiliary Circuit:	Solid 2x1...4 mm ² Flexible with Insulated Ferrule 1x0.75...2.5 mm ² Stranded 2x1...4 mm ² Flexible 2x0.75...2.5 mm ² Flexible with Ferrule 2x0.75...2.5 mm ²
Connecting Capacity Main Circuit:	Flexible 2x10...70 mm ² Rigid Cu-Cable 2x10...95 mm ²
Connecting terminals (delivered in open position):	YES
Connecting terminals (delivered in open position) Coils terminals:	YES
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 160 A
Country of Origin:	Sweden (SE)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	1SFC101070D0201
Declaration of Conformity - CE:	2CMT004242
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Dimension Diagram:	1SFB535001G1051
Drop-out Voltage in % of Uc:	55 %
E-number:	3210068
EAN:	7320500476376

EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / Contactors
EPLAN Function Definition:	NC contact / NC contact, 2 connection points / NC auxiliary contact 21_22 NO contact / NO contact, 2 connection points / NO auxiliary contact 13_14 NO contact / NO contact, 2 connection points / Power NO contact 5_6 Coil / Coil, 2 connection points / Coil for power contactor A1_A2
ETIM 4:	EC000066 - Magnet contactor, AC-switching
ETIM 5:	EC000066 - Magnet contactor, AC-switching
ETIM 6:	EC000066 - Power contactor, AC switching
Environmental Information:	2CMT004732
Full Load Amps Motor Use:	(440 ... 480 V AC) Three Phase 96 A (550 ... 600 V AC) Three Phase 99 A
General Use Rating UL/CSA:	(600 V AC) 160 A
Horsepower Rating UL/CSA:	(208 V AC) Three Phase 30 Hp (440 ... 480 V AC) Three Phase 75 Hp (550 ... 600 V AC) Three Phase 100 Hp (220 ... 240 V AC) Three Phase 40 Hp (200 V AC) Three Phase 30 Hp
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SFC100003M0201
Invoice Description:	AF116-30-11-13 Contactor
Made To Order:	No
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 2000 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 1000 A
Maximum Electrical Switching Frequency:	AC-3 300 cycles per hour AC-1 300 cycles per hour AC-2 / AC-4 150 cycles per hour
Maximum Mechanical Switching Frequency:	300 cycles per hour
Maximum Operating Altitude Permissible:	3000 m
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Mechanical Durability:	5 million
Minimum Order Quantity:	1 piece
Mounted Auxiliary Contacts:	1 NO, 1 NC
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Main Contacts NC:	0
Number of Main Contacts NO:	3
Number of Poles:	3
Object Classification Code:	Q
Operate Time:	Between Coil Energization and NO Contact Closing 25...55 ms Between Coil De-energization and NO Contact Opening 37...47 ms
Order Multiple:	1 piece
Package Level 1 EAN:	7320500476376
Package Level 1 Gross Weight:	1.57 kg
Package Level 1 Height:	169 mm
Package Level 1 Length:	115 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	194 mm
Part Type:	New
Power Loss:	at Rated Operating Conditions per Pole 6 W
Product Main Type:	AF116

Product main type:	AF 110
Product Name:	Contactora
Product Net Depth:	126.0 mm
Product Net Height:	150.0 mm
Product Net Weight:	1.644 kg
Product Net Width:	90.0 mm
Product Packing Type:	Box
Quote Only:	No
RINA Certificate:	ELE060313XG/002
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1:	8 x I _e AC-3
Rated Control Circuit Voltage (U_c):	60 Hz 100...250 V 50 Hz 100...250 V DC Operation 100...250 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Frequency Limits:	25...400 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Making Capacity AC-3 acc. to IEC 60947-4-1:	10 x I _e AC-3
Rated Operational Current AC-1 (I_e):	(690 V) 55 °C 145 A (690 V) 40 °C 160 A (690 V) 70 °C 130 A
Rated Operational Current AC-3 (I_e):	(690 V) 55 °C 65 A (415 V) 55 °C 116 A (220 / 230 / 240 V) 55 °C 116 A (440 V) 55 °C 116 A (380 / 400 V) 55 °C 116 A (500 V) 55 °C 110 A
Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Current DC-3 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Current DC-5 (I_e):	(110 V) 2 Poles in Series, 40 °C 145 A (220 V) 3 Poles in Series, 40 °C 145 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 30 kW (380 / 400 V) 55 kW (415 V) 55 kW (440 V) 75 kW (500 V) 75 kW (690 V) 55 kW
Rated Operational Voltage:	Main Circuit 690 V
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 160 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 536 A at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 928 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1160 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 379 A
RoHS Date:	1226 1
RoHS Information:	1SFC101055D0202
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	AF116-30-11-13 100-250V 50/60Hz / DC Contactora
Short-Circuit Protective Devices:	gG Type Fuses 250 A
Technical Information:	Mechanically

Terminal Type: Double Clamp

Tightening Torque: Cable Lug 9 N·m
Main Circuit 8 N·m

UNSPSC: 39121529

