

General Information

Extended Product Type:	AF30-30-00-13
Product ID:	1SBL277001R1300
EAN:	3471523111233
Catalog Description:	AF30-30-00-13 100-250V50/60HZ-DC Contactor
Long Description:	AF30 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage $U_c \text{ min} \dots U_c \text{ max}$. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.

Additional Information

ABB Industrial IT Suite:	Control IT
ABS Certificate:	ABS_15-GE1349500-PDA_90682247
Ambient Air Temperature:	Close to Contactor for Storage -60...+80 °C Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C Close to Contactor without Thermal O/L Relay -40 ... +70 °C
Block Contactor Type:	3-Pole Contactor
CB Certificate:	CB_SE_70856M1
CCC Certificate:	CCC_2010010304445623
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Coil Voltage Code:	13
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Connecting Capacity Main Circuit:	Flexible with Insulated Ferrule 1x 1.5...10 mm ² Flexible with Insulated Ferrule 2x 1.5...4 mm ² Flexible with Ferrule 1/2x 1.5...10 mm ² Rigid 1/2x 2.5...10 mm ²
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 50 A
Country of Origin:	France (FR)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	1SBC101411D0201
Declaration of Conformity - CE:	1SBD250000U1000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
E-number:	3211382
EAC Certificate:	EAC_RU C-FR ME77 B01010
EAN:	3471523111233
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / Contactors
EPLAN Function Definition:	Coil / Coil, 2 connection points / Coil for power contactor A1_A2 NO contact / NO contact, 2 connection points / Power NO contact 1_2 NO contact / NO contact. 2 connection points / Power NO contact 3 4

NO contact / NO contact, 2 connection points / Power NO contact 5_6

EPLAN Macro:	9AKK106930A0699
ETIM 4:	EC000066 - Magnet contactor, AC-switching
ETIM 5:	EC000066 - Magnet contactor, AC-switching
ETIM 6:	EC000066 - Power contactor, AC switching
Environmental Information:	1SBD250149E1000
Full Load Amps Motor Use:	(120 V AC) Single Phase 24 A (240 V AC) Single Phase 28 A (200 ... 208 V AC) Three Phase 32.2 A (220 ... 240 V AC) Three Phase 28 A (440 ... 480 V AC) Three Phase 27 A (550 ... 600 V AC) Three Phase 27 A
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
General Use Rating UL/CSA:	(600 V AC) 50 A
Horsepower Rating UL/CSA:	(120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (200 ... 208 V AC) Three Phase 10 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 25 Hp
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SBC101027M6801
Invoice Description:	AF30-30-00-13 100-250V50/60HZ-DC Contactor
LR Certificate:	LRS_1300087E1
Low Coil Consumption:	No
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 500 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 200 A
Maximum Electrical Switching Frequency:	AC-1 600 cycles per hour AC-2 / AC-4 150 cycles per hour AC-3 1200 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Maximum Operating Altitude Permissible:	3000 m
Minimum Order Quantity:	1 piece
Mounted Auxiliary Contacts:	0 NO, 0 NC
Mounted Auxiliary Contacts 1st Stack:	0 NO, 0 NC
Mounted Auxiliary Contacts 2nd Stack:	0 NO, 0 NC
Mounting Position:	Max. N.C. built-in and add-on N.C. auxiliary contacts: see accessory fitting details for a 3-pole contactor AF09 ... AF38
Mounting Positions:	1SBC500297F0000
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Main Contacts NC:	0
Number of Main Contacts NO:	3
Object Classification Code:	Q
Operate Time:	Between Coil De-energization and NC Contact Closing 13...98 ms Between Coil De-energization and NO Contact Opening 11...95 ms Between Coil Energization and NC Contact Opening 38...90 ms Between Coil Energization and NO Contact Closing 40...95 ms
Order Multiple:	1 piece
Package Level 1 EAN:	3471523111233
Package Level 1 Gross Weight:	0.31 kg

Package Level 1 Height:	47 mm
Package Level 1 Length:	87 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	87 mm
Package Level 2 Height:	315 mm
Package Level 2 Length:	300 mm
Package Level 2 Units:	45 piece
Package Level 2 Width:	250 mm
Package Level 3 Units:	1080 piece
Power Loss:	at Rated Operating Conditions AC-1 per Pole 2.4 W at Rated Operating Conditions AC-3 per Pole 0.9 W
Product Main Type:	AF30
Product Name:	Block Contactor
Product Net Depth:	86 mm
Product Net Height:	86 mm
Product Net Weight:	0.310 kg
Product Net Width:	45 mm
Product Packing Type:	Box
RINA Certificate:	RINA_ELE084013XG
RMRS Certificate:	RMRS_1400682124
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 50 A (690 V) 60 °C 42 A (690 V) 70 °C 37 A
Rated Operational Current AC-3 (I_e):	(220 / 230 / 240 V) 60 °C 33 A (380 / 400 V) 60 °C 32 A (415 V) 60 °C 32 A (440 V) 60 °C 32 A (500 V) 60 °C 28 A (690 V) 60 °C 21 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 9 kW (380 / 400 V) 15 kW (400 V) 15 kW (415 V) 15 kW (440 V) 18.5 kW (500 V) 18.5 kW (690 V) 18.5 kW
Rated Operational Voltage:	Main Circuit 690 V
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 350 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 50 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 700 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g

Resistance to Vibrations acc. to IEC 60068-2-6:	5 ... 300 Hz 4 g closed position / 2 g open position
RoHS Date:	20090609
RoHS Information:	1SBD251012E1000
Selling Unit of Measure:	piece
Short Description:	AF30-30-00-13 100-250V50/60HZ-DC Contactor
Standards:	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
Terminal Type:	Screw Terminals
Tightening Torque:	Control Circuit 1.2 N·m Main Circuit 2.5 N·m
Tightening Torque UL/CSA:	Control Circuit 11 in·lb Main Circuit 22 in·lb
UL Certificate:	UL_20140305-E312527_7_1
UL Listing Card:	UL_E312527
UNSPSC:	39121529
Wire Stripping Length:	Control Circuit 10 mm Main Circuit 14 mm
DNV GL Certificate:	DNV-GL_E13871

