

Products Low Voltage Products and Systems Control Products Contactors Block Contactors

### General Information

<b>Extended Product Type:</b>	AF52-40-00-13
<b>Product ID:</b>	1SBL367201R1300
<b>EAN:</b>	3471523133631
<b>Catalog Description:</b>	AF52-40-00-13 100-250V50/60HZ-DC Contactor
<b>Long Description:</b>	AF52 4-pole contactors are used for controlling power circuits up to 690 V AC and 440 V DC. They are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...). AF... contactors include an electronic coil interface accepting a wide control voltage $U_c$ min. ... $U_c$ max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.

### Additional Information

<b>ABB Industrial IT Suite:</b>	Control IT
<b>ABS Certificate:</b>	ABS_15-GE1349500-PDA_90682247
<b>Ambient Air Temperature:</b>	Close to Contactor for Storage -60...+80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
<b>Block Contactor Type:</b>	4-Pole Contactor
<b>CB Certificate:</b>	CB_SE_77418
<b>Climatic Withstand:</b>	Category B according to IEC 60947-1 Annex Q
<b>Coil Voltage Code:</b>	13
<b>Connecting Capacity Control Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Connecting Capacity Main Circuit:</b>	Flexible with Ferrule 1/2x 4...35 mm <sup>2</sup> Rigid 1/2x 6...35 mm <sup>2</sup>
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 105 A
<b>Country of Origin:</b>	France (FR)
<b>Customs Tariff Number:</b>	85364900
<b>Declaration of Conformity - CE:</b>	1SBD250001U1000
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
<b>E-number:</b>	3210311
<b>EAN:</b>	3471523133631
<b>EPLAN Catalog Tree:</b>	Electrical engineering / Relays, contactors / Contactors
<b>EPLAN Function Definition:</b>	Coil / Coil, 2 connection points / Coil for power contactor A1_A2 NO contact / NO contact, 2 connection points / Power NO contact 1_2 NO contact / NO contact, 2 connection points / Power NO contact 3_4 NO contact / NO contact, 2 connection points / Power NO contact 5_6 NO contact / NO contact, 2 connection points / Power NO contact 7_8
<b>EPLAN Macro:</b>	9AKK106930A0718
<b>ETIM 4:</b>	EC000066 - Magnet contactor, AC-switching
<b>ETIM 5:</b>	EC000066 - Magnet contactor, AC-switching
<b>ETIM 6:</b>	EC000066 - Power contactor, AC switching
<b>Full Load Amps Motor Use:</b>	(120 V AC) Single Phase 34 A

(240 V AC) Single Phase 50 A  
(200 ... 208 V AC) Three Phase 48.3 A  
(220 ... 240 V AC) Three Phase 54 A  
(440 ... 480 V AC) Three Phase 52 A  
(550 ... 600 V AC) Three Phase 52 A

<b>General Use Rating UL/CSA:</b>	(600 V AC) 80 A
<b>Horsepower Rating UL/CSA:</b>	(120 V AC) Single Phase 3 Hp (240 V AC) Single Phase 10 Hp (200 ... 208 V AC) Three Phase 15 Hp (220 ... 240 V AC) Three Phase 20 Hp (440 ... 480 V AC) Three Phase 40 Hp (550 ... 600 V AC) Three Phase 50 Hp
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SBC101047M6801
<b>Invoice Description:</b>	AF52-40-00-13 100-250V50/60HZ-DC Contactor
<b>LR Certificate:</b>	LRS_1300087E1
<b>Low Coil Consumption:</b>	No
<b>Maximum Breaking Capacity:</b>	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 600 A
<b>Maximum Electrical Switching Frequency:</b>	AC-1 600 cycles per hour
<b>Maximum Mechanical Switching Frequency:</b>	3600 cycles per hour
<b>Maximum Operating Altitude Permissible:</b>	3000 m
<b>Minimum Order Quantity:</b>	1 piece
<b>Mounted Auxiliary Contacts:</b>	0 NO, 0 NC
<b>Mounting Position:</b>	Max. add-on N.C. auxiliary contacts: see accessory fitting details for a 4-pole contactor AF40 ... AF96
<b>Mounting Positions:</b>	1SBC500297F0000
<b>Number of Auxiliary Contacts NC:</b>	0
<b>Number of Auxiliary Contacts NO:</b>	0
<b>Number of Main Contacts NC:</b>	0
<b>Number of Main Contacts NO:</b>	4
<b>Object Classification Code:</b>	Q
<b>Order Multiple:</b>	1 piece
<b>Package Level 1 EAN:</b>	3471523133631
<b>Package Level 1 Gross Weight:</b>	1.27 kg
<b>Package Level 1 Height:</b>	103 mm
<b>Package Level 1 Length:</b>	150 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	150 mm
<b>Package Level 2 Height:</b>	300 mm
<b>Package Level 2 Length:</b>	300 mm
<b>Package Level 2 Units:</b>	8 piece
<b>Package Level 2 Width:</b>	250 mm
<b>Package Level 3 Units:</b>	192 piece
<b>Packing Type:</b>	Box
<b>Power Loss:</b>	at Rated Operating Conditions AC-1 per Pole 6.3 W at Rated Operating Conditions AC-3 per Pole 1.7 W
<b>Product Main Type:</b>	AF52
<b>Product Name:</b>	Block Contactor
<b>Product Net Depth:</b>	113.5 mm

<b>Product Net Height:</b>	125.5 mm
<b>Product Net Weight:</b>	1.16 kg
<b>Product Net Width:</b>	70 mm
<b>Product Packing Type:</b>	Box
<b>RMRS Certificate:</b>	RMRS_1400682124
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
<b>Rated Frequency (f):</b>	Main Circuit 50 / 60 Hz
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6 kV
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
<b>Rated Operational Current AC-1 (I<sub>b</sub>):</b>	(690 V) 40 °C 100 A (690 V) 60 °C 80 A (690 V) 70 °C 70 A
<b>Rated Operational Current AC-3 (I<sub>b</sub>):</b>	(220 / 230 / 240 V) 60 °C 53 A (380 / 400 V) 60 °C 53 A (415 V) 60 °C 53 A (440 V) 60 °C 53 A (500 V) 60 °C 45 A (690 V) 60 °C 35 A
<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(220 / 230 / 240 V) 15 kW (380 / 400 V) 22 kW (415 V) 30 kW (440 V) 30 kW (500 V) 30 kW (690 V) 30 kW
<b>Rated Operational Voltage:</b>	Main Circuit 690 V
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5 ... 300 Hz 3 g Closed position / 2 g Open position
<b>Selling Unit of Measure:</b>	piece
<b>Short Description:</b>	AF52-40-00-13 100-250V50/60HZ-DC Contactor
<b>Terminal Type:</b>	Screw Terminals
<b>UL Certificate:</b>	UL_20141124-E312527-14-2
<b>UL Listing Card:</b>	UL_E312527
<b>UNSPSC:</b>	39121529
<b>Wire Stripping Length:</b>	Main Circuit 16 mm



