

AF370-30-11-13



Products Low Voltage Products and Systems Control Products Contactors Block Contactors

General Information

Extended Product Type:	AF370-30-11-13
Product ID:	1SFL607002R1311
EAN:	7320500481899
Catalog Description:	AF370-30-11-13 Contactor
Long Description:	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 1000 V. Operated with wide control voltage range 100-250 V, 50/60 Hz and DC

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40...+70 °C Close to Contactor for Storage -40...+70 °C
Battery Information:	Type NONE
Block Contactor Type:	3-Pole Contactor
CB Certificate:	SE-73044M1
Coil Consumption:	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 385 V·A Holding at Max. Rated Control Circuit Voltage DC 4.5 W Holding at Max. Rated Control Circuit Voltage 50 Hz 17.5 V·A Pull-in at Max. Rated Control Circuit Voltage DC 410 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 385 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 17.5 V·A
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 x Uc Min. ... 1.1 x Uc Max. (at $\theta \leq 70$ °C) °C
Coil Voltage Code:	13
Connecting Capacity:	Rigid Al-Cable 1x185...240 mm ² Flexible 2x70...185 mm ² Rigid Cu-Cable 2x70...185 mm ²
Connecting Capacity Auxiliary Circuit:	Solid 2x1...4 mm ² Flexible with Insulated Ferrule 2x0.75...2.5 mm ² Stranded 1x1...4 mm ² Flexible 2x0.75...2.5 mm ² Flexible with Ferrule 2x0.75...2.5 mm ²
Connecting Capacity Main Circuit:	Rigid Al-Cable 1x185...240 mm ² Flexible 2x70...185 mm ² Rigid Cu-Cable 2x70...185 mm ²
Connecting terminals (delivered in open position):	YES
Connecting terminals (delivered in open position) Coils terminals:	YES
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 600 A
Country of Origin:	Sweden (SE)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	1SFC101070D0201
Declaration of Conformity - CE:	2CMT004749
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Drop-out Voltage in % of Uc:	55 %
E-number:	3210171
EAN:	7320500481899

EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / Contactors
EPLAN Function Definition:	NC contact / NC contact, 2 connection points / NC auxiliary contact 21_22 NO contact / NO contact, 2 connection points / NO auxiliary contact 13_14 NO contact / NO contact, 2 connection points / Power NO contact 5_6 Coil / Coil, 2 connection points / Coil for power contactor A1_A2
ETIM 4:	EC000066 - Magnet contactor, AC-switching
ETIM 5:	EC000066 - Magnet contactor, AC-switching
ETIM 6:	EC000066 - Power contactor, AC switching
Environmental Information:	2CMT004732
Full Load Amps Motor Use:	(440 ... 480 V AC) Three Phase 361 A (550 ... 600 V AC) Three Phase 336 A
General Use Rating UL/CSA:	(600 V AC) 520 A
Horsepower Rating UL/CSA:	(208 V AC) Three Phase 125 Hp (440 ... 480 V AC) Three Phase 300 Hp (550 ... 600 V AC) Three Phase 350 Hp (220 ... 240 V AC) Three Phase 150 Hp (200 V AC) Three Phase 125 Hp
IT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SFC100008M0201
Invoice Description:	AF370-30-11-13 Contactor
Made To Order:	No
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 5000 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 4000 A
Maximum Electrical Switching Frequency:	AC-3 300 cycles per hour AC-1 300 cycles per hour AC-2 / AC-4 150 cycles per hour
Maximum Mechanical Switching Frequency:	300 cycles per hour
Maximum Operating Altitude Permissible:	3000 m
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Mechanical Durability:	5 million
Minimum Order Quantity:	1 piece
Mounted Auxiliary Contacts:	1 NO, 1 NC
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Main Contacts NC:	0
Number of Main Contacts NO:	3
Number of Poles:	3
Object Classification Code:	Q
Operate Time:	Between Coil Energization and NO Contact Closing 25...55 ms Between Coil De-energization and NO Contact Opening 37...47 ms
Order Multiple:	1 piece
Package Level 1 EAN:	7320500481899
Package Level 1 Gross Weight:	5.31 kg
Package Level 1 Height:	270 mm
Package Level 1 Length:	175 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	223 mm
Part Type:	New
Power Loss:	at Rated Operating Conditions per Pole 27 W
Product Main Type:	AF370

Product Name:	Contactor
Product Net Depth:	180.0 mm
Product Net Height:	225.0 mm
Product Net Weight:	4.640 kg
Product Net Width:	140.0 mm
Product Packing Type:	Box
Quote Only:	No
RINA Certificate:	ELE060313XG/002
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1:	8 x I _e AC-3
Rated Control Circuit Voltage (U_c):	60 Hz 100...250 V 50 Hz 100...250 V DC Operation 100...250 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Rated Frequency Limits:	25...400 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Making Capacity AC-3 acc. to IEC 60947-4-1:	10 x I _e AC-3
Rated Operational Current AC-1 (I_e):	(690 V) 55 °C 500 A (690 V) 40 °C 600 A (1000 V) 40 °C 400 A (1000 V) 55 °C 350 A (690 V) 70 °C 400 A (1000 V) 70 °C 290 A
Rated Operational Current AC-3 (I_e):	(1000 V) 55 °C 100 A (690 V) 55 °C 315 A (415 V) 55 °C 370 A (220 / 230 / 240 V) 55 °C 370 A (440 V) 55 °C 370 A (380 / 400 V) 55 °C 370 A (500 V) 55 °C 315 A
Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A
Rated Operational Current DC-3 (I_e):	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A
Rated Operational Current DC-5 (I_e):	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 110 kW (380 / 400 V) 200 kW (415 V) 200 kW (440 V) 200 kW (500 V) 250 kW (690 V) 315 kW (1000 V) 132 kW
Rated Operational Voltage:	Main Circuit 1000 V
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1709 A at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2960 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3700 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 1208 A
RoHS Date:	1226 1
RoHS Information:	1SFC101055D0202
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece

Short Description:	AF370-30-11-13 100-250V 50/60Hz / DC Contactor
Short-Circuit Protective Devices:	gG Type Fuses 630 A
Technical Information:	Mechanically
Terminal Type:	Main Circuit: Bars
Tightening Torque:	Cable Lug 28 N·m Main Circuit 22...43 N·m
UNSPSC:	39121529