

General Information

Extended Product Type:	T16-1.0
Product ID:	1SAZ711201R1023
EAN:	4013614397875
Catalog Description:	T16-1.0 Thermal Overload Relay
Long Description:	The T16-1.0 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the mini contactors or block contactors. Single mounting kits are available as accessory.

Additional Information

ABS Certificate:	1SAA941001-0102
Ambient Air Temperature:	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation:	Yes
Ampere Rating UL/CSA:	1 A
BV Certificate:	1SAA941001-0202
CB Certificate:	1SAA941008-2001
CCC Certificate:	1SAA941005-3802
Co-ordination with Short-Circuit Protective Devices - Type 1:	gG Type Fuses 6 A
Co-ordination with Short-Circuit Protective Devices - Type 2:	gG Type Fuses 6 A
Connecting Capacity Auxiliary Circuit UL/CSA:	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
Connecting Capacity Main Circuit UL/CSA:	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-10 AWG
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm ² Flexible 1/2x 0.75 ... 4 mm ² Solid 1/2x 0.75 ... 1.5 mm ² Solid 1/2x 1.5 ... 4 mm ² Stranded 1/2x 1 ... 4 mm ²
Contact Rating UL/CSA:	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Conventional Free-air Thermal Current (I_{th}):	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Country of Origin:	Germany (DE)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC106020D0201
Data Sheet, Technical Information (Part 2):	1SAZ700505E0000

Data Sheet, Technical Information (Part 2):	1SAZ700000F0000
Declaration of Conformity - CE:	1SAD938506-0182
Degree of Protection:	IP20
Dimension Diagram:	1SAZ700404F0001
E-number:	3212061
EAC Certificate:	1SAA941002-2701
EAN:	4013614397875
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
EPLAN Function Definition:	NO contact / NO contact, 2 connection points / NO auxiliary contact 97_98 NC contact / NC contact, 2 connection points / NC auxiliary contact 95_96 Overload / Thermal release, 6 connection points / Thermal release (bimetal relay) 1_2_3_4_5_6
ETIM 4:	EC000106 - Thermal overload relay
ETIM 5:	EC000106 - Thermal overload relay
ETIM 6:	EC000106 - Thermal overload relay
GL Certificate:	1SAA941007-0401
GOST Certificate:	1SAA941000-2704
IT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC106019M6802 2CDC106021M6801
Invoice Description:	T16-1.0 Thermal Overload Relay Trip class 10, 0.74-1.00 A
LR Certificate:	1SAA941001-0502
Maximum Operating Altitude Permissible:	2000 m
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 5
Mounting Type:	Mounted on Contactor
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Number of Poles:	3
Number of Protected Poles:	3
Object Classification Code:	F
Package Level 1 EAN:	4013614397875
Package Level 1 Gross Weight:	0.112 kg
Package Level 1 Height:	63 mm
Package Level 1 Length:	82 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	48 mm
Package Level 2 EAN:	4013614440588
Package Level 2 Gross Weight:	8.45 kg
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Units:	72 piece
Package Level 2 Width:	280 mm
Phase Loss Sensitive:	Yes
Pollution Degree:	3
Power Loss:	at Rated Operating Conditions per Pole 1.1 ... 2.0 W
Product Main Type:	T16
Product Name:	Thermal Overload Relay

Product Net Depth:	53.5 mm
Product Net Height:	76.7 mm
Product Net Weight:	0.1 kg
Product Net Width:	45 mm
RINA Certificate:	1SAA941000-0801
RMRS Certificate:	1SAA941000-0703
Rated Current (I_n):	1 A
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U_i):	690 V
Rated Operational Current (I_e):	1 A
Rated Operational Current AC-15 (I_e):	(120 V) NC 3 A (120 V) NO 0.75 A (240 V) NC 3 A (240 V) NO 0.75 A (400 V) NC 0.75 A (400 V) NO 0.75 A (500 V) NC 0.75 A (500 V) NO 0.75 A
Rated Operational Current AC-3 (I_e):	1 A
Rated Operational Current DC-13 (I_e):	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
Rated Operational Voltage:	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC
Recommended Screw Driver:	Main Circuit Pozidriv 2
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 22g
Resistance to Vibrations acc. to IEC 60068-2-6:	3g / 3 ... 150 Hz
RoHS Date:	1360
RoHS Information:	1SAA941005-4402
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Setting Range:	0.74 ... 1 A
Short Description:	T16-1.0 Thermal Overload Relay
Short-Circuit Protective Devices:	Auxiliary Circuit NC - gG Type Fuses 6 A Auxiliary Circuit NO - gG Type Fuses 4 A
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Suitable For:	B6

BC6
B7
BC7
VB6
VBC6
VB7
VBC7
AS09
AS12
AS16

Suitable for Product Class: Block Contactors
Mini Contactors

Terminal Type: Screw Terminals

Tightening Torque: Auxiliary Circuit 1 ... 1.2 N·m
Main Circuit 1.1 ... 1.5 N·m

Tightening Torque UL/CSA: Auxiliary Circuit 9 ... 11 in·lb
Main Circuit 9 ... 13 in·lb

Trip Class: 10

UL Certificate: UL_E48139

UNSPSC: 39121521

Wire Stripping Length: Auxiliary Circuit 9 mm
Main Circuit 12 mm

cUL Certificate: cUL_E48139

eClass: 7.0 27371501

DNV GL Certificate: 1SAA941001-0302
