

General Information

Extended Product Type:	S1-M3-35
Product ID:	1SAM201913R1103
EAN:	4013614400834
Catalog Description:	S1-M3-35 Power Infeed Block
Long Description:	S1-M3-35 3-phase power infeed block Flat, for MS116 / MS132, 35mm ² , Type E

Additional Information

Accessory Type:	3-Phase Power Infeed Block
Ambient Air Temperature:	Operation -25 ... +70 °C Storage -50 ... +80 °C
Ampere Rating UL/CSA:	92 A
Connecting Capacity Main Circuit UL/CSA:	Flexible 1x 14-6 AWG Stranded 1x 14-4 AWG
Connecting Capacity Main Circuit:	Flexible 1x 10 ... 35 mm ² Rigid 1x 10 ... 35 mm ²
Country of Origin:	Germany (DE)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SBC100192C02--
Declaration of Conformity - CE:	1SAD938510-0056
Degree of Protection:	IP20
E-number:	3112083
EAN:	4013614400834
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC000275 - Rail terminal bar
ETIM 6:	EC000275 - Rail terminal bar
GOST Certificate:	1SAA937000-2703
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Invoice Description:	S1-M3-35 3-phase power infeed block Flat, for MS116 / MS132, 35mm ² , Type E
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Minimum Order Quantity:	1 piece
Number of Poles:	3
Object Classification Code:	X
Package Level 1 EAN:	4013614488221
Package Level 1 Gross Weight:	0.638 kg
Package Level 1 Height:	38 mm
Package Level 1 Length:	245 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	59 mm
Product Main Type:	S1
Product Name:	Power Infeed Block
Product Net Depth:	35.3 mm

Product Net Height:	45.7 mm
Product Net Weight:	0.06 kg
Product Net Width:	45.5 mm
Rated Operational Current (I_e):	100 A
Rated Operational Voltage:	690 V Main Circuit 690 V
Recommended Screw Driver:	Hexgon SW4
RoHS Date:	0159
RoHS Information:	1SAA963003-4402
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	S1-M3-35 3-phase power infeed block
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS325 MO325
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Main Circuit 4.5 N·m
Tightening Torque UL/CSA:	Main Circuit 40 in·lb
UL Certificate:	1SAA963001-1602
UNSPSC:	39120000
Wire Stripping Length:	Main Circuit 12 mm
cUL Certificate:	1SAA963001-1701
eClass:	7.0 27400603

