

Products Low Voltage Products and Systems Control Products Manual Motor Starters Manual Motor Starters Accessories

Parts & Services Drives Medium voltage AC drives Industrial drives ACS2000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS1000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS5000

Parts & Services Drives Medium voltage AC drives Special purpose drives ACS6000

General Information

Extended Product Type:	PS1-2-0-65
Product ID:	1SAM201906R1102
EAN:	4013614400681
Catalog Description:	PS1-2-0-65 Busbar
Long Description:	PS1-2-0-65 3-phase busbar for 2 MS116 / MS132, Ie=65A

Additional Information

Accessory Type:	3-Phase Busbar
Ambient Air Temperature:	Operation -25 ... +70 °C Storage -50 ... +80 °C
Ampere Rating UL/CSA:	65 A
Country of Origin:	Germany (DE)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SBC100192C02--
Declaration of Conformity - CE:	1SAD938510-0056
Degree of Protection:	IP20
Dimension Diagram:	1SAM200450F0001
E-number:	3111675
EAN:	4013614400681
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC000215 - Phase busbar
ETIM 6:	EC000215 - Phase busbar
GOST Certificate:	1SAA937000-2703
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Invoice Description:	PS1-2-0-65 3-phase busbar for 2 MS116 / MS132, Ie=65A
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
Minimum Order Quantity:	1 piece
Object Classification Code:	W
Package Level 1 EAN:	4013614488061
Package Level 1 Gross Weight:	0.37 kg
Package Level 1 Height:	46 mm
Package Level 1 Length:	120 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	80 mm
Product Main Type:	PS1
Product Name:	Busbar

Product Name:	Busbar
Product Net Depth:	13 mm
Product Net Height:	32.3 mm
Product Net Weight:	0.034 kg
Product Net Width:	86.5 mm
Rated Operational Current (I_e):	65 A
Rated Operational Voltage:	690 V Main Circuit 690 V
RoHS Date:	0159
RoHS Information:	1SAA963003-4402
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	PS1-2-0-65 3-phase busbar
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS116 MS132
Suitable for Product Class:	Manual Motor Starter
UL Certificate:	1SAA963001-1602
UNSPSC:	39121100
cUL Certificate:	1SAA963001-1701
eClass:	7.0 27371306

Where Used (as a spare part for "Products")

4 Products		Filter	<input type="text"/>
Identifier	Description	Qty	Unit Of Measure
ACS 1000	No Description Available	1	piece
ACS 2000	No Description Available	1	piece
ACS 5000 Water Cooled	No Description Available	1	piece
ACS 6000	No Description Available	1	piece

Product specific part data

4 Products		Filter	<input type="text"/>
Product	Category	Drive Part Category	
ACS 2000	ACS2000	Mechanics (Busbars, Isolators etc.)	
ACS 1000	ACS1000	Mechanics (Busbars, Isolators etc.)	
ACS 5000 Water Cooled	ACS5000	Mechanics (Busbars, Isolators etc.)	
ACS 6000	ACS6000	Mechanics (Busbars, Isolators etc.)	

