FS Spacer Clamp, Snap Close - FS24 (553550)












- Provides support for ERIFLEX FLEXIBAR and insulated braided conductors without damaging the insulation
- Ensures correct spacing for optimum cooling
- Supports up to four conductors in parallel
- Easy to install
- Halogen free
- RoHS compliant









Part Number	FS24
Article Number	553550
Material	Polyamide
Working Temperature	-40 to 130 °C
Flammability Rating	UL® 94HB
Conductor Width	24 mm Max
Height (H)	53 mm
Length (L)	30 mm
Hole Size (HS)	7 mm
Unit Weight	0.015 kg
Certifications	EAC 8546901000 (Russian Federation) RoHS UR
Standard Packaging Quantity	25 pc
UPC	78285644978
EAN-13	3479775535500

Recommended distance between supports is 400 mm [15 3/4"].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. WARNING Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty. © 2017 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

ERIFLEX

PENTAIR