

# OS63GB03P



Products Low Voltage Products and Systems Switches Switch Fuses

## General Information

<b>Extended Product Type:</b>	OS63GB03P
<b>Product ID:</b>	1SCA115235R1001
<b>EAN:</b>	6417019476605
<b>Catalog Description:</b>	OS63GB03P Switch fuse
<b>Long Description:</b>	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

## Additional Information

<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	q = 40 °C 63 A
<b>Country of Origin:</b>	Finland (FI)
<b>Customs Tariff Number:</b>	85365080
<b>Data Sheet, Technical Information:</b>	1SCC311013C0201
<b>Declaration of Conformity - CE:</b>	1SCC311136D0201
<b>EAN:</b>	6417019476605
<b>ETIM 5:</b>	EC001040 - Fuse switch disconnecter
<b>Environmental Information:</b>	1SCC311002D0201
<b>Fuse Size:</b>	A2-A3
<b>Fuse System:</b>	British Standard
<b>Fuse Type:</b>	BS
<b>Handle Type:</b>	Handle and shaft included
<b>IT Publishing Status:</b>	Level 0 - Information enabled
<b>Includes:</b>	Handle and Shaft
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SCC311036M0204
<b>Invoice Description:</b>	OS63GB03P Switch fuse
<b>Minimum Order Quantity:</b>	1 piece
<b>Mounting Type:</b>	Base mounting
<b>Number of Poles:</b>	3
<b>Object Classification Code:</b>	Q
<b>Switches Operating Mechanism:</b>	03 (Left Side)
<b>Operating Mode:</b>	Front Operated
<b>Package Level 1 EAN:</b>	6417019476605
<b>Package Level 1 Gross Weight:</b>	1.2 kg
<b>Package Level 1 Height:</b>	137 mm
<b>Package Level 1 Length:</b>	192 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	146 mm
<b>Pollution Degree:</b>	3
<b>Position of Line Terminals:</b>	Top In - Bottom Out
<b>Power Loss:</b>	4 W
<b>Price Category:</b>	Standard
<b>Product Main Type:</b>	OS63
<b>Product Name:</b>	Switch fuse
<b>Product Net Depth:</b>	100 mm

Product Net Depth:	109 mm
Product Net Height:	125 mm
Product Net Weight:	1.2 kg
Product Net Width:	112 mm
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	12 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Current AC-21A ( $I_e$ ):	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A ( $I_e$ ):	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A ( $I_e$ ):	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Power AC-23A ( $P_e$ ):	(380 ... 415 V) 30 kW (500 V) 37 kW (690 V) 55 kW
Rated Operational Voltage:	690 V AC
RoHS Information:	1SCC311138D0201
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
Selling Unit of Measure:	piece
Short Description:	Switch fuse 63 A, Front operated, 3-pole, for BS fuse type, fuse size A2-A3
Standards:	IEC 60947-3
Terminal Type:	Screw Terminals

