

OS125GB22N1P



Products Low Voltage Products and Systems Switches Switch Fuses

General Information

Extended Product Type:	OS125GB22N1P
Product ID:	1SCA115903R1001
EAN:	6417019481722
Catalog Description:	OS125GB22N1P Switch fuse
Long Description:	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

Additional Information

Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 125 A
---	-----------------

Country of Origin:	Finland (FI)
--------------------	--------------

Customs Tariff Number:	85365080
------------------------	----------

Data Sheet, Technical Information:	1SCC311013C0201
------------------------------------	-----------------

Declaration of Conformity - CE:	1SCC311137D0201
---------------------------------	-----------------

EAN:	6417019481722
------	---------------

ETIM 5:	EC001040 - Fuse switch disconnecter
---------	-------------------------------------

Environmental Information:	1SCC311002D0201
----------------------------	-----------------

Fuse Size:	A2-A4
------------	-------

Fuse System:	British Standard
--------------	------------------

Fuse Type:	BS
------------	----

Handle Type:	Handle and shaft included
--------------	---------------------------

IIT Publishing Status:	Level 0 - Information enabled
------------------------	-------------------------------

Includes:	Handle and Shaft
-----------	------------------

Industrial IT Certification Level:	0
------------------------------------	---

Instructions and Manuals:	1SCC311037M0202
---------------------------	-----------------

Invoice Description:	OS125GB22N1P Switch fuse
----------------------	--------------------------

Minimum Order Quantity:	1 piece
-------------------------	---------

Mounting Type:	Base mounting
----------------	---------------

Number of Poles:	4
------------------	---

Object Classification Code:	Q
-----------------------------	---

Switches Operating Mechanism:	22 (Between the Poles)
-------------------------------	------------------------

Operating Mode:	Front Operated
-----------------	----------------

Package Level 1 EAN:	6417019481722
----------------------	---------------

Package Level 1 Gross Weight:	2.0 kg
-------------------------------	--------

Package Level 1 Height:	159 mm
-------------------------	--------

Package Level 1 Length:	242 mm
-------------------------	--------

Package Level 1 Units:	1 piece
------------------------	---------

Package Level 1 Width:	192 mm
------------------------	--------

Pollution Degree:	3
-------------------	---

Position of Line Terminals:	Top In - Bottom Out
-----------------------------	---------------------

Power Loss:	5 W
-------------	-----

Price Category:	Standard
-----------------	----------

Product Main Type:	OS125
--------------------	-------

Product Name:	Switch fuse
---------------	-------------

Product Net Depth:	115 mm
--------------------	--------

Product Net Depth:	115 mm
Product Net Height:	140 mm
Product Net Weight:	2.0 kg
Product Net Width:	182 mm
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_b):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A (I_b):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A (I_b):	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Power AC-23A (P_e):	(380 ... 415 V) 55 kW (500 V) 75 kW (690 V) 110 kW
Rated Operational Voltage:	690 V AC
RoHS Information:	1SCC311138D0201
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
Selling Unit of Measure:	piece
Short Description:	Switch fuse 125 A, Front operated, 4-pole, for BS fuse type, fuse size A2-A4
Standards:	IEC 60947-3
Terminal Type:	Lug terminals
Fourth Pole Type:	Switched - With Solid Link
Fourth Pole Position:	Left Side

