

# OS200B04N2P



Products Low Voltage Products and Systems Switches Switch Fuses

## General Information

Extended Product Type:	OS200B04N2P
Product ID:	1SCA022709R9410
EAN:	6417019225876
Catalog Description:	OS200B04N2P Switch fuse
Long Description:	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

## Additional Information

BV Certificate:	1SCC311103D0201
Conventional Free-air Thermal Current ( $I_{th}$ ):	q = 40 °C 200 A
Conventional Thermal Current ( $I_{the}$ ):	Fully Enclosed 200 A
Country of Origin:	Finland (FI)
Customs Tariff Number:	85365080
Data Sheet, Technical Information:	1SCC311013C0201
Declaration of Conformity - CE:	1SCC311091D0201
EAN:	6417019225876
ETIM 5:	EC001040 - Fuse switch disconnecter
Environmental Information:	1SCC311002D0201
Fuse Size:	B1-B2
Fuse System:	British Standard
Fuse Type:	BS
GL Certificate:	1SCC311097D0201
Handle Type:	Handle and shaft included
IIT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Industrial IT Certification Level:	0
Instructions and Manuals:	1SCC311012M0011
Invoice Description:	OS200B04N2P Switch fuse
LR Certificate:	1SCC311102D0201
Minimum Order Quantity:	1 piece
Mounting Type:	Base mounting
Number of Poles:	4
Object Classification Code:	Q
Switches Operating Mechanism:	04 (Left Side)
Operating Mode:	Front Operated
Order Multiple:	1 piece
Package Level 1 EAN:	6417019225876
Package Level 1 Gross Weight:	4.2 kg
Package Level 1 Height:	163 mm
Package Level 1 Length:	280 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	210 mm
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole & W

Power Loss:	at Rated Operating Conditions per Pole 0 W
Price Category:	Standard
Product Main Type:	OS200
Product Name:	Switch fuse
Product Net Depth:	132 mm
Product Net Height:	199 mm
Product Net Weight:	4.2 kg
Product Net Width:	182 mm
Rated Operational Current AC-21A ( $I_b$ ):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A ( $I_b$ ):	(500 V) 200 A (380 ... 415 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A ( $I_b$ ):	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Power AC-23A ( $P_e$ ):	(380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Rated Operational Voltage:	690 V AC
RoHS Information:	1SCC311108D0202
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-05-01
Selling Unit of Measure:	piece
Short Description:	Switch fuse, Front operated, 4-pole, for BS fuse type, sizes B1, B2
Standards:	IEC 60947-3
Terminal Type:	Lug terminals
Fourth Pole Type:	Switched - With Solid Link
Fourth Pole Position:	Right Side

