

# OS250B04N2P



Products Low Voltage Products and Systems Switches Switch Fuses

## General Information

<b>Extended Product Type:</b>	OS250B04N2P
<b>Product ID:</b>	1SCA022750R7800
<b>EAN:</b>	6417019244075
<b>Catalog Description:</b>	OS250B04N2P Switch fuse
<b>Long Description:</b>	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

## Additional Information

<b>BV Certificate:</b>	1SCC311103D0201
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	q = 40 °C 250 A
<b>Conventional Thermal Current (<math>I_{the}</math>):</b>	Fully Enclosed 250 A
<b>Country of Origin:</b>	Finland (FI)
<b>Customs Tariff Number:</b>	85365080
<b>Data Sheet, Technical Information:</b>	1SCC311013C0201
<b>Declaration of Conformity - CE:</b>	1SCC311091D0201
<b>EAN:</b>	6417019244075
<b>ETIM 5:</b>	EC001040 - Fuse switch disconnecter
<b>Environmental Information:</b>	1SCC311002D0201
<b>Fuse Size:</b>	B1-B3
<b>Fuse System:</b>	British Standard
<b>Fuse Type:</b>	BS
<b>GL Certificate:</b>	1SCC311097D0201
<b>Handle Type:</b>	Handle and shaft included
<b>IT Publishing Status:</b>	Level 0 - Information enabled
<b>Includes:</b>	Handle and Shaft
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SCC311012M0011
<b>Invoice Description:</b>	OS250B04N2P Switch fuse
<b>LR Certificate:</b>	1SCC311102D0201
<b>Minimum Order Quantity:</b>	1 piece
<b>Mounting Type:</b>	Base mounting
<b>Number of Poles:</b>	4
<b>Object Classification Code:</b>	Q
<b>Switches Operating Mechanism:</b>	04 (Left Side)
<b>Operating Mode:</b>	Front Operated
<b>Order Multiple:</b>	1 piece
<b>Package Level 1 EAN:</b>	6417019244075
<b>Package Level 1 Gross Weight:</b>	5.1 kg
<b>Package Level 1 Height:</b>	167 mm
<b>Package Level 1 Length:</b>	316 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	204 mm
<b>Position of Line Terminals:</b>	Top In - Bottom Out
<b>Power Loss:</b>	at Rated Operating Conditions per Pole 13 W

Power Loss:	at Rated Operating Conditions per Pole 13 w
Price Category:	Standard
Product Main Type:	OS250
Product Name:	Switch fuse
Product Net Depth:	154 mm
Product Net Height:	193 mm
Product Net Weight:	5.1 kg
Product Net Width:	262 mm
Rated Operational Current AC-21A ( $I_b$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A ( $I_b$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A ( $I_b$ ):	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A ( $P_e$ ):	(380 ... 415 V) 140 kW (500 V) 170 kW (690 V) 250 kW
Rated Operational Voltage:	690 V AC
RoHS Information:	1SCC311108D0202
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-05-01
Selling Unit of Measure:	piece
Short Description:	Switch fuse, Front operated, 4-pole, for BS fuse type, sizes B1, B2, B3
Standards:	IEC 60947-3
Terminal Type:	Lug terminals
Fourth Pole Type:	Switched - With Solid Link
Fourth Pole Position:	Right Side

