

Products Low Voltage Products and Systems Switches Switch Fuses

General Information

Extended Product Type:	OS315B03P
Product ID:	1SCA022719R0680
EAN:	6417019230658
Catalog Description:	OS315B03P Switch fuse
Long Description:	Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

Additional Information

BV Certificate:	1SCC311103D0201
Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 315 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 315 A
Country of Origin:	Finland (FI)
Customs Tariff Number:	85365080
Data Sheet, Technical Information:	1SCC311013C0201
Declaration of Conformity - CE:	1SCC311099D0201
EAN:	6417019230658
ETIM 5:	EC001040 - Fuse switch disconnecter
Environmental Information:	1SCC311002D0201
Fuse Size:	B1-B4
Fuse System:	British Standard
Fuse Type:	BS
GL Certificate:	1SCC311097D0201
Handle Type:	Handle and shaft included
IT Publishing Status:	Level 0 - Information enabled
Includes:	Handle and Shaft
Industrial IT Certification Level:	0
Instructions and Manuals:	1SCC311015M0006
Invoice Description:	OS315B03P Switch fuse
LR Certificate:	1SCC311102D0201
Minimum Order Quantity:	1 piece
Mounting Type:	Base mounting
Number of Poles:	3
Object Classification Code:	Q
Switches Operating Mechanism:	03 (Left Side)
Operating Mode:	Front Operated
Order Multiple:	1 piece
Package Level 1 EAN:	6417019230658
Package Level 1 Gross Weight:	7.1 kg
Package Level 1 Height:	206 mm
Package Level 1 Length:	270 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	240 mm
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	at Rated Operating Conditions per Pole 10 W

Power Loss:	at Rated Operating Conditions per Pole 19 W
Price Category:	Standard
Product Main Type:	OS315
Product Name:	Switch fuse
Product Net Depth:	176 mm
Product Net Height:	230 mm
Product Net Weight:	7.1 kg
Product Net Width:	255 mm
Rated Operational Current AC-21A (I_b):	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-22A (I_b):	(500 V) 315 A (380 ... 415 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_b):	(500 V) 315 A (380 ... 415 V) 315 A (690 V) 315 A
Rated Operational Power AC-23A (P_b):	(380 ... 415 V) 160 kW (500 V) 220 kW (690 V) 315 kW
Rated Operational Voltage:	690 V AC
RoHS Information:	1SCC311108D0202
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-05-01
Selling Unit of Measure:	piece
Short Description:	Switch fuse, Front operated, 3-pole, for BS fuse type, sizes B1, B2, B3, B4
Standards:	IEC 60947-3
Terminal Type:	Lug terminals

