

## General Information

<b>Extended Product Type:</b>	JB6-4
<b>Product ID:</b>	1SNK906304R0000
<b>EAN:</b>	3472599097636
<b>Catalog Description:</b>	JB6-4 Jumper Bar - Orange
<b>Long Description:</b>	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV).

## Additional Information

<b>ABB Industrial IT Suite:</b>	Control IT
<b>ATEX Certificate:</b>	1SND162004A1707
<b>Ambient Air Temperature:</b>	Operation -55 ... +110 °C Storage -55 ... +110 °C
<b>Ambient Temperature:</b>	-5 ... +40 °C
<b>CB Certificate:</b>	1SND161025A0203
<b>Color:</b>	Orange
<b>Country of Origin:</b>	France (FR)
<b>Customs Tariff Number:</b>	85369010
<b>Data Sheet, Technical Information:</b>	1SNK160029D0201
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Dielectric Test Voltage:</b>	2200 V
<b>E-nummer:</b>	2925374
<b>EAN:</b>	3472599097636
<b>ETIM 4:</b>	EC000489 - Cross-connector for terminal block
<b>ETIM 5:</b>	EC000489 - Cross-connector for terminal block
<b>ETIM 6:</b>	EC000489 - Cross-connector for terminal block
<b>Flammability According to UL94:</b>	V0
<b>Function:</b>	Jumper Bars
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SNK160027C0201
<b>Insulation Material:</b>	Polyamide
<b>Invoice Description:</b>	JB6-4 Jumper Bar - Orange
<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>Medium Description:</b>	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for various configurations, - Insulated, - Positive locking.
<b>Minimum Order Quantity:</b>	50 piece
<b>Number of Poles:</b>	4
<b>Object Classification Code:</b>	X
<b>Order Multiple:</b>	50 piece
<b>Package Level 1 EAN:</b>	3472599097636
<b>Package Level 1 Gross Weight:</b>	0.145 kg
<b>Package Level 1 Height:</b>	50 mm
<b>Package Level 1 Length:</b>	117 mm
<b>Package Level 1 Units:</b>	50 piece
<b>Package Level 1 Width:</b>	50 mm

Package Level 2 Units:	1500 piece
Package Level 3 Units:	144000 piece
Pollution Degree:	3
Power Loss:	1.3 W
Product Main Type:	JB6
Product Name:	Jumper Bar
Product Net Depth:	26.8 mm
Product Net Height:	21 mm
Product Net Length:	26.8 mm
Product Net Weight:	2.9 g
Product Net Width:	6 mm
Rated Current (I <sub>n</sub> ):	Main Circuit 41 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 720 A
Rated Voltage (U <sub>r</sub> ):	1000 V
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Date:	18 08 2005
RoHS Information:	1SND230499F0202
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	Jumper Bars JB6-4
Spacing:	6 mm
Sub-Function 2:	Screwless
Suitable For:	ZDK4-22 ZDS4-22-R1 ZK2.5-SF ZK2.5-SF-R ZK2.5-S-R1 ZK4 ZK4-3P ZK4-4P ZK4-PE ZK4-PE-3P ZK4-PE-4P ZS4-PE-R2 ZS4-R2 ZS4-SF ZS4-SF-R ZS4-SF-T ZS4-SP-R1 ZS4-SP-T2-R1 ZS4-S-R1 ZS4-S-R2 ZS4-S-T-R1 ZS4-T3-R1 ZS6 ZS6-3S ZS6-3S-PE ZS6-4S ZS6-4S-PE ZS6-D1 ZS6-D1-PE Z