




<b>Technical Data Sheet:</b>	<b>DS204/0912</b>
<b>Product Description</b>	<b>Plated steel conduit fixing clip with PVC liner - P clip</b>
<b>Product Range</b>	<b>FCC - P clip</b>

Roman Way, Coleshill  
Birmingham  
B46 1HG, United Kingdom  
Tel: 00 44 (0)1675 466900  
Website: www.flexicon.uk.com



**Material;**

Bright zinc plated to BS1706  
Black PVC to BS2571

**Fire Performance:**

Self Extinguishing

**IP Rating:**

N/A

**Applications:**

Suitable for fixing flexible conduits to ensure a neat installation.

**Temperature Performance:**

-20°C to +105°C

Part Number-Plated Steel with PVC liner	Conduit Size	Nominal ID mm (A)	Width mm (B)	Width mm (C)	Fixing Hole mm (D)
FCC10	10	11.0	12.7	17.4	5.1
FCC12	12	14.0	12.7	17.4	5.1
FCC16	16	17.0	12.7	17.4	5.1
FCC20	20	21.0	12.7	17.4	5.1
FCC25	25	25.0	12.7	17.4	5.1
FCC32	32	34.0	12.7	17.4	5.1
FCC40	40	44.0	25.4	30.5	14.2 X 17.5
FCC50	50	54.0	25.4	30.5	14.2 X 17.5
FCC63	63	70.0	25.4	30.5	14.2 X 17.5
FCC75	75	76.2	25.4	30.5	14.2 X 17.5

**Compliance, Approvals & Accreditation;**



**Typical Applications;**



Construction



Rail



Machinery and OEM's



Defence

Errors, omissions and amendments excepted. As part of continuing product development Flexicon Ltd reserve the right to alter product specifications without prior notice. Data given is correct at time of compilation. Product specification and application data is for guidance only and does not constitute a warranty of any kind, either expressed or implied for Flexicon products or their suitability for a specific purpose. Third party approvals maybe limited to certain sizes within a product range.