

S201M-D10



Products Low Voltage Products and Systems Modular DIN Rail Products Miniature Circuit Breakers MCBs

General Information

Extended Product Type:	S201M-D10
Product ID:	2CDS271001R0101
EAN:	4016779599429
Catalog Description:	Miniature Circuit Breaker - S200M - 1P - D - 10 A
Long Description:	System pro M compact S200M miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200M comply with IEC/EN 60898-1 and IEC/EN 609 47-2, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200M to save 50% space.

Additional Information

Actuator Material:	Insulation Group II, Black, Sealable
Actuator Type:	Insulation group II, black, sealable
Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +70 °C
Built-In Depth (t₂):	69 mm
Connecting Capacity:	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Connecting Capacity UL/CSA:	Busbar 14-8 AWG Conductor 14-4 AWG
Contact Position Indication:	Red ON / Green OFF
Country of Origin:	Germany (DE)
Customs Tariff Number:	85362010
Data Sheet, Technical Information:	2CSC400002D0208
Declaration of Conformity - CE:	2CDK403001D0604
Degree of Protection:	IP20
Dielectric Test Voltage:	50 / 60 Hz, 1 min: 2 kV
E-number:	2100034
EAN:	4016779599429
EPLAN Catalog Tree:	Electrical engineering / Protection devices / General
EPLAN Function Definition:	Circuit breaker / Single circuit breaker / Circuit breaker 1_2
EPLAN Macro:	9AKK106713A8090
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)
Electrical Endurance:	20000 AC cycle
Energy Limiting Class:	3
Environmental Conditions:	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Environmental Information:	2CDK400030D0201
Housing Material:	Insulation Group II, RAL 7035
Installation Size:	acc. to DIN 43880 1

Instructions and Manuals:	2CSC400002D0208
Interrupting Rating acc. to UL1077:	(277 V AC) 6 kA (60 V DC) 10 kA
Invoice Description:	S201M-D 10 Miniature Circuit Breaker D-Char.,10kA,10A,1P
Maximum Operating Voltage UL/CSA:	480Y / 277 V AC
Mechanical Endurance:	20000 cycle
Minimum Order Quantity:	1 piece
Mounting Position:	Any
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Poles:	1
Number of Protected Poles:	1
Object Classification Code:	F
Operational Voltage:	Maximum (Incl. Tolerance) 253 V AC Maximum (Incl. Tolerance) 72 V DC Maximum 253 V AC Maximum 72 V DC Minimum 12 V AC Minimum 12 V DC
Overvoltage Category:	III
Package Level 1 EAN:	4016779602280
Package Level 1 Gross Weight:	1.295 kg
Package Level 1 Height:	80 mm
Package Level 1 Length:	183 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	92 mm
Package Level 2 EAN:	4016779975544
Package Level 2 Gross Weight:	11.92 kg
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Units:	120 piece
Package Level 2 Width:	275 mm
Pole Net Weight:	0.115 kg
Pollution Degree:	3
Power Loss:	1.6 W at Rated Operating Conditions per Pole 1.6 W
Power Supply Connection:	Arbitrary
Product Main Type:	S200M
Product Name:	Miniature Circuit Breaker
Product Net Depth:	69 mm
Product Net Height:	88 mm
Product Net Weight:	0.125 kg
Product Net Width:	17.5 mm
Rated Current (I_n):	10 A
Rated Frequency (f):	50 Hz 60 Hz
Rated Impulse Withstand Voltage (U_{imp}):	4 kV (6.2 kV @ sea level) (5.0 kV @ 2000 m)
Rated Insulation Voltage (U_i):	acc. to IEC/EN 60664-1 440 V
Rated Operational Voltage:	acc. to IEC 60898-1 230 / 400 V AC

acc. to IEC 60947-2 230 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(133 V AC) 18.8 kA
Rated Short-Circuit Capacity (I_{cn}):	(230 / 400 V AC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(133 V AC) 25 kA (230 V AC) 15 kA
Recommended Screw Driver:	Pozidriv 2
Reference Ambient Air Temperature:	30 °C
Remarks:	IP40 in enclosure with cover
Resistance to Shock acc. to IEC 60068-2-27:	25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6:	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
RoHS Date:	0335
RoHS Information:	2CDK400003K0201
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Screw Terminal Type:	Failsafe Bi-directional Cylinder-lift Terminal
Selling Unit of Measure:	piece
Short Description:	S201M-D 10 Miniature Circuit Breaker
Standards:	IEC/EN 60898-1 IEC/EN 60947-2
Terminal Type:	Screw Terminals
Tightening Torque:	2 N·m
Tightening Torque UL/CSA:	18 in·lb
Tripping Characteristic:	D
UNSPSC:	39121614
Width in Number of Modular Spacings:	1
eClass:	7.0 27141901
Accessories Available:	Yes

Accessories

32 Products

Filter

Identifier	Description	Type	Qty	Unit Of Measure
2CCA880100R0001	CMS-100PS Sensore 18mm, 80A	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensore 18mm, 40A	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensore 18mm, 20A	CMS-102PS	1	piece
2CDS200909R0001	S2C-A1 - Bobina a lancio di corrente	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 - Bobina a lancio di corrente	S2C-A2	1	piece
2CDS200912R0001	S2C-H6R - Contatto ausiliario	S2C-H6R	1	piece
2CDS200918R0001	S2C-NT - Hand Operated Neutral	S2C-NT	1	piece
2CDS200922R0001	S2C-S/H6R - Contatto di segnalazione / ausiliario	S2C-S/H6R	1	piece
2CDS200936R0001	S2C-H11L - Contatto ausiliario	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L - Contatto ausiliario	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L - Contatto ausiliario	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R - Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-11L - Auxiliary Contact	S2C-H6-11L	1	piece

2CDS200946R0002 Identifier	S2C-H6-ZUR - Auxiliary Contact Description	S2C-H6-ZUR Type	1 Qty	piece Unit Of Measure
2CDS200946R0003	S2C-H6-02R - Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200970R0001	S2C-H01 - Contatto ausiliario	S2C-H01	1	piece
2CDS200970R0002	S2C-H10 - Contatto ausiliario	S2C-H10	1	piece
2CSS200911R0001	S2C-UA 12 DC - Undervoltage release	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC - Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC - Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC - Undervoltage release	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC - Undervoltage release	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC - Undervoltage release	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC - Undervoltage release	S2C-UA 230 DC	1	piece
2CSS200998R0001	S2C-BP - Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST - Plug-in base	S2C-EST	1	piece
2CSS201997R0013	S2C-CM1 - Motor operating device	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 - Motor operating device	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 - Motor operating device	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH - Accessori meccanici	S2C-DH	1	piece

