



Main

Range of product	NSX100...250 PowerPact multistandard NSX400...630 DC NSX400...630 Easypact CVS400...630 Easypact CVS100...250 NSX100...250 DC
Range compatibility	NSX100...250 Easypact CVS400...630 NSX100...250 DC NSX400...630 DC NSX400...630 Easypact CVS100...250 PowerPact Multistandard
Product or component type	Voltage release
Device short name	MX
Voltage release type	Shunt trip release
Control circuit voltage	48 V AC


Complementary

Control signal type	Impulse Maintained
Impulse duration	≥ 20 ms
Threshold tripping voltage	$0.7 \dots 1.1 \times U_n$ - during opening time
Supply inrush power	30 W
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal ≤ 1.5 mm ²

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0819 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
