



### Main

Range of product	PowerPact multistandard NSX100...250 NSX400...630 Easypact CVS400...630 NSX400...630 DC NSX100...250 DC Easypact CVS100...250
Range compatibility	NSX100...250 NSX100...250 DC NSX400...630 NSX400...630 DC Easypact CVS100...250 Easypact CVS400...630 PowerPact Multistandard
Product or component type	Voltage release
Device short name	MX
Voltage release type	Shunt trip release
Control circuit voltage	12 V DC


### Complementary

Control signal type	Impulse Maintained
Impulse duration	$\geq 20$ ms
Threshold tripping voltage	$0.7 \dots 1.1 \times U_n$ - during opening time
Supply inrush power	30 VA
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal $\leq 1.5$ mm <sup>2</sup>

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0819 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available  <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------