



### Main

Range of product	Easypact CVS100...250 Easypact CVS400...630 NSX400...630 DC NSX100...250 NSX400...630 PowerPact multistandard NSX100...250 DC
Range compatibility	NSX100...250 DC NSX400...630 DC NSX100...250 Easypact CVS400...630 Easypact CVS100...250 NSX400...630 PowerPact Multistandard
Product or component type	Voltage release
Device short name	MN
Voltage release type	Undervoltage release
Control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz

### Complementary

Threshold tripping voltage	0.85 x Un - during closing time 0.35...0.7 x Un - during opening time
Supply holding power	5 W
Supply inrush power	30 W
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal <= 1.5 mm <sup>2</sup>

### Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0835 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------