

690 Volt Industrial Fuse-links to IEC 60269-2/BS 88-2

Rated Voltages 690V a.c. 250V d.c.(min) • Breaking Capacities 80kA a.c. 40kA d.c. • Breaking Ranges and Utilisation Category gG/gM



Offset Tag Fuse-links

BS 88 Ref.	Current Rating (A)	List Ref.	Fixing Centres G1	
			mm	ins
A1	2	SSA1 2	44.5	1%
	4	SSA1 4		
	6	SSA1 6		
	10	SSA1 10		
	16	SSA1 16		
A2	2	SSA2 2	73	2%
	4	SSA2 4		
	6	SSA2 6		
	10	SSA2 10		
	16	SSA2 16		
	20	SSA2 20		
A3	40	SSA3 40	73	2%
	50	SSA3 50		
	63	SSA3 63		
A4	32	SSA4 32	94	3 1/4%
	40	SSA4 40		
	50	SSA4 50		
	63	SSA4 63		
	80	SSA4 80		
(as A4)	125	SSFP 125	94	3 1/4%
	160	SSFP 160		
	200	SSFP 200		

Offset Tag Fuse-links

BS 88 Ref.	Current Rating (A)	List Ref.	Fixing Centres G1		Fixing Centres G2	
			mm	ins	mm	ins
-	355	85SSM 355	102	4	22	%
	400	85SSM 400				
	450	86SST 450				
	500	86SST 500				
-	560	86SST 560	102	4	22	%
	630	86SST 630				
	670	86SST 670				
-	710	86SST 710	102	4	22	%
	750	86SST 750				
	800	86SST 800				

Central Tag Fuse-links

BS 88 Ref.	Current Ratings (A)	List Ref.	Fixing Centres G1		Fixing Centres G2	
			mm	ins	mm	ins
	2	SSB 2	97	3 1/4%	-	
	4	SSB 4				
	6	SSB 6				
	10	SSB 10				
	16	SSB 16				
	20	SSB 20				
	25	SSB 25				
	32	SSB 32				
	40	SSB 40				
	50	SSB 50				
	63	SSB 63				
(asB1)	2	SSBC 2	111	4%	-	
	4	SSBC 4				
	6	SSBC 6				
	10	SSBC 10				
	16	SSBC 16				
	20	SSBC 20				
	25	SSBC 25				
B1	80	SSB1 80	111	4%	-	
	100	SSB1 100				
B2	125	SSB2 125	111	4%	-	
	160	SSB2 160				
	200	SSB2 200				
-	125	84SSF 125	99	4 1/2%	-	
	160	84SSF 160				
	200	84SSF 200				
B3	250	SSB3 250	111	4%	-	
	315	SSB3 315				
-	250	84SSK 250	133	3 3/4%	-	
	315	84SSK 315				
-	250	SSKM 250	133	5%	-	
	315	SSKM 315				
B4	355	SSB4 355	111	4%	-	
	400	SSB4 400				
C1	355	SSC1 355	133	5%	184	7 1/4%
	400	SSC1 400				
-	355	SSMT 355	165	6%	229	9
	400	SSMT 400				
	450	SSC2 450				
	500	SSC2 500				
C2	560	SSC2 560	133	5%	184	7 1/4%
	630	SSC2 630				
	450	SST 450				
	500	SST 500				
-	560	SST 560	165	6 1/2%	229	9
	630	SST 630				
	670	SSC3 670				
	710	SSC3 710				
C3	750	SSC3 750	133	5%	184	7 1/4%
	800	SSC3 800				
	670	SSLT 670				
	710	SSLT 710				
-	750	SSLT 750	165	6%	229	9
	800	SSLT 800				
	450	SSLU 450				
	500	SSLU 500				
D1	560	SSLU 560	149	5%	32	1%
	630	SSLU 630				
	670	SSLU 670				
	710	SSLU 710				
	750	SSLU 750				
	800	SSLU 800				

Dimensions and current ratings of the Lawson type SS Industrial Fuse-links comply with the standardized requirements of IEC 60269-2 and BS 88-2.

Additional types and current ratings are included in the range.

Lawson type SS Industrial Fuse-links can be fitted in Boltin Fuse-holders (see page 15) or suitable fusegear.