

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | JB8-5 |
| Product ID: | 1SNK908305R0000 |
| EAN: | 3472599097704 |
| Catalog Description: | JB8-5 Jumper Bar - Orange |
| Long Description: | Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV). |

Additional Information

| | |
|---|--|
| ABB Industrial IT Suite: | Control IT |
| ATEX Certificate: | 1SND162004A1707 |
| Ambient Air Temperature: | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| Ambient Temperature: | -5 ... +40 °C |
| CB Certificate: | 1SND161018A0202 |
| Color: | Orange |
| Country of Origin: | France (FR) |
| Customs Tariff Number: | 85369010 |
| Data Sheet, Technical Information: | 1SNK160030D0201 |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Dielectric Test Voltage: | 2200 V |
| E-nummer: | 2925381 |
| EAN: | 3472599097704 |
| ETIM 4: | EC000489 - Cross-connector for terminal block |
| ETIM 5: | EC000489 - Cross-connector for terminal block |
| ETIM 6: | EC000489 - Cross-connector for terminal block |
| Flammability According to UL94: | V0 |
| Function: | Jumper Bars |
| IIT Publishing Status: | Level 0 - Information enabled |
| Industrial IT Certification Level: | 0 |
| Instructions and Manuals: | 1SNK160027C0201 |
| Insulation Material: | Polyamide |
| Invoice Description: | JB8-5 Jumper Bar - Orange |
| Maximum Operating Voltage UL/CSA: | Main Circuit 600 V |
| Medium Description: | Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for various configurations, - Insulated, - Positive locking. |
| Minimum Order Quantity: | 40 piece |
| Number of Poles: | 5 |
| Object Classification Code: | X |
| Order Multiple: | 40 piece |
| Package Level 1 EAN: | 3472599097704 |
| Package Level 1 Gross Weight: | 0.28 kg |
| Package Level 1 Height: | 50 mm |
| Package Level 1 Length: | 117 mm |
| Package Level 1 Units: | 40 piece |
| Package Level 1 Width: | 50 mm |

| | |
|--|---|
| Package Level 2 Units: | 1200 piece |
| Package Level 3 Units: | 115200 piece |
| Pollution Degree: | 3 |
| Power Loss: | 1.8 W |
| Product Main Type: | JB8 |
| Product Name: | Jumper Bar |
| Product Net Depth: | 27.8 mm |
| Product Net Height: | 37.6 mm |
| Product Net Length: | 27.8 mm |
| Product Net Weight: | 7 g |
| Product Net Width: | 8 mm |
| Rated Current (I_n): | Main Circuit 57 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 6000 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 1200 A |
| Rated Voltage (U_r): | 1000 V |
| Resistance to Vibrations acc. to IEC 60068-2-6: | Compliant |
| RoHS Date: | 18 08 2005 |
| RoHS Information: | 1SND230499F0202 |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Selling Unit of Measure: | piece |
| Short Description: | Jumper Bars JB8-5 |
| Spacing: | 8 mm |
| Sub-Function 2: | Screwless |
| Suitable For: | ZK6 ZK6-3P ZK6-PE ZK6-PE-3P ZS10 ZS10-SF ZS10-SF-R ZS10-S-R2 ZS4-D2-SF1 ZS4-D2-SF1-R |

