

General Information

Extended Product Type:	JB16-2
Product ID:	1SNK916302R0000
EAN:	3472599163027
Catalog Description:	JB16-2 Jumper Bar - Orange
Long Description:	Insulated jumper bar with screw mounting.

Additional Information

ABB Industrial IT Suite:	Control IT
ATEX Certificate:	1SND162004A1707
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Ambient Temperature:	-5 ... +40 °C
CB Certificate:	1SND161028A0202
Color:	Orange
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNK160032D0201
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2200 V
E-nummer:	2925388
EAN:	3472599163027
ETIM 4:	EC000489 - Cross-connector for terminal block
ETIM 5:	EC000489 - Cross-connector for terminal block
ETIM 6:	EC000489 - Cross-connector for terminal block
Flammability According to UL94:	V0
Function:	Jumper Bars
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	JB16-2 Jumper Bar - Orange
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Medium Description:	Insulated jumper bar with screw mounting.
Minimum Order Quantity:	10 piece
Mounting Type:	- With flat pliers, cut out the partitions on the terminal block insulating body. Be careful to not cut out the jumpered terminal blocks partitions at both ends of the assembly in order to maintain the IP20, Nema1 protection and insulation, - Install the jumper bar with the recommended tool and torque.
Number of Poles:	2
Object Classification Code:	X
Order Multiple:	10 piece
Package Level 1 EAN:	3472599163027
Package Level 1 Gross Weight:	0.1 kg
Package Level 1 Height:	5 mm
Package Level 1 Length:	170 mm
Package Level 1 Units:	10 piece

Package Level 1 Width:	125 mm
Package Level 2 Height:	200 mm
Package Level 2 Length:	300 mm
Package Level 2 Units:	1000 piece
Package Level 2 Width:	200 mm
Package Level 3 Units:	48000 piece
Pollution Degree:	3
Power Loss:	4 W
Product Main Type:	JB16
Product Name:	Jumper Bar
Product Net Depth:	23.4 mm
Product Net Height:	27.5 mm
Product Net Length:	23.4 mm
Product Net Weight:	10 g
Product Net Width:	16 mm
Product Packing Type:	Bag
Rated Current (I_n):	Main Circuit 125 A
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 4200 A
Rated Voltage (U_r):	1000 V
Recommended Screw Driver:	5.5 mm
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Date:	18 08 2005
RoHS Information:	1SND230499F0202
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	Jumper Bars JB16-2
Spacing:	16 mm
Sub-Function 2:	Screw
Suitable For:	M35/16 ZS35 ZS50 ZS50-PE

