

General Information

Extended Product Type:	JB10-4
Product ID:	1SNK910304R0000
EAN:	3472599097742
Catalog Description:	JB10-4 Jumper Bar - Orange
Long Description:	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV).

Additional Information

ABB Industrial IT Suite:	Control IT
ATEX Certificate:	1SND162004A1707
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Ambient Temperature:	-5 ... +40 °C
CB Certificate:	1SND161021A0201
Color:	Orange
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNK160031D0201
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2200 V
E-nummer:	2925385
EAN:	3472599097742
ETIM 4:	EC000489 - Cross-connector for terminal block
ETIM 5:	EC000489 - Cross-connector for terminal block
ETIM 6:	EC000489 - Cross-connector for terminal block
Flammability According to UL94:	V0
Function:	Jumper Bars
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	JB10-4 Jumper Bar - Orange
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Medium Description:	Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for various configurations, - Insulated, - Positive locking.
Minimum Order Quantity:	40 piece
Number of Poles:	4
Object Classification Code:	X
Order Multiple:	40 piece
Package Level 1 EAN:	3472599097742
Package Level 1 Gross Weight:	0.376 kg
Package Level 1 Height:	50 mm
Package Level 1 Length:	117 mm
Package Level 1 Units:	40 piece
Package Level 1 Width:	50 mm

Package Level 2 Units:	1200 piece
Package Level 3 Units:	115200 piece
Pollution Degree:	3
Power Loss:	2.4 W
Product Main Type:	JB10
Product Name:	Jumper Bar
Product Net Depth:	31.5 mm
Product Net Height:	30.8 mm
Product Net Length:	31.5 mm
Product Net Weight:	9.4 g
Product Net Width:	10 mm
Rated Current (I_n):	Main Circuit 76 A
Rated Impulse Withstand Voltage (U_{imp}):	6000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 1920 A
Rated Voltage (U_r):	1000 V
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Date:	18 08 2005
RoHS Information:	1SND230499F0202
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	Jumper Bars JB10-4
Spacing:	10 mm
Sub-Function 2:	Screwless
Suitable For:	ZK10 ZK10-3P ZK10-PE ZK10-PE-3P ZS16

