JB16-10



Products Low Voltage Products and Systems Connection Devices Terminal Blocks Accessories Jumper Bars

General Information

Extended Product Type: JB16-10

 Product ID:
 1SNK916310R0000

 EAN:
 3472599163102

Catalog Description: JB16-10 Jumper Bar - Orange

Long Description: Insulated jumper bar with screw mounting.

Additional Information

ABB Industrial IT Suite:	Control IT
ATEX Certificate:	1SND162004A1707
Ambient Air Temperature:	Operation -55 +110 °C Storage -55 +110 °C
Ambient Temperature:	-5 +40 °C
CB Certificate:	1SND161028A0202
Color:	Orange
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNK160032D0201
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2200 V
E-nummer:	2925392
EAN:	3472599163102
ЕПМ 4:	EC000489 - Cross-connector for terminal block
ETIM 5:	EC000489 - Cross-connector for terminal block
ЕТІМ 6:	EC000489 - Cross-connector for terminal block
Flammability According to UL94:	V0
Function:	Jumper Bars
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	JB16-10 Jumper Bar - Orange
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Medium Description:	Insulated jumper bar with screw mounting.
Minimum Order Quantity:	10 piece
Mounting Type:	- With flat pliers, cut out the partitions on the terminal block insulating body. Be careful to not cut out the jumpered terminal blocks partitions at both ends of the assembly in order to maint ain the IP20, Nema1 protection and insulation, - Install the jumper bar with the recommended tool and torque.
Number of Poles:	10
Object Classification Code:	X
Order Multiple:	10 piece
Package Level 1 EAN:	3472599163102
Package Level 1 Gross Weight:	0.566 kg
Package Level 1 Height:	5 mm
Package Level 1 Length:	300 mm
Package Level 1 Units:	10 piece

•
200 mm
200 mm
300 mm
250 piece
200 mm
12000 piece
3
4 W
JB16
Jumper Bar
23.4 mm
155.5 mm
23.4 mm
56.6 g
30.0 g
16 mm
16 mm
16 mm Bag
16 mm Bag Main Circuit 125 A
16 mm Bag Main Circuit 125 A 8000 V
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant 18 08 2005
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant 18 08 2005 1SND230499F0202
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant 18 08 2005 1SND230499F0202 Following EU Directive 2002/95/EC August 18, 2005 and amendment
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant 18 08 2005 1SND230499F0202 Following EU Directive 2002/95/EC August 18, 2005 and amendment piece
16 mm Bag Main Circuit 125 A 8000 V for 1 s 4200 A 1000 V 5.5 mm Compliant 18 08 2005 1SND230499F0202 Following EU Directive 2002/95/EC August 18, 2005 and amendment piece Jumper Bars JB16-10



ZS35