

Products Low Voltage Products and Systems Connection Devices Terminal Blocks SNA Series

General Information

Extended Product Type:	D95/26
Product ID:	1SNA400370R2400
EAN:	3472594003700
Catalog Description:	D95/26 Screw Clamp Terminal Blocks - Feed-through - Grey
Long Description:	- Closed terminal block: no end section needed, optimized rigidity, - Use of jumper bars requires the user to cut-out the partition.

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Ambient Temperature:	-5 ... +40 °C
CSA Certificate:	1SND161051A0202
Color:	Grey
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 2 ... 0000 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 2 ... 0000 AWG Stranded 0 AWG
Connecting Capacity Main Circuit:	Screw Clamp / Flexible 1x 35 ... 95 mm ² Screw Clamp / Rigid 1x 35 ... 120 mm ² Screw Clamp / With Insulated Ferrule 1x 50 mm ²
Connection Type:	Screw clamp
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNC160019C0202
Declaration of Conformity - CE:	1SND225014U1000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
EAC Certificate:	1SND161009A1100
EAN:	3472594003700
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block
Environmental Information:	1SND220001E1002
Function:	Feed-through
Gauge Type:	B12
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNC160019C0202
Insulation Material:	Polyamide
Invoice Description:	D95/26 Screw Clamp Terminal Blocks - Feed-through - Grey
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Minimum Order Quantity:	10 piece
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Object Classification Code:	X
Order Multiple:	10 piece

Package Level 1 EAN:	3472594003700
Package Level 1 Gross Weight:	2.15 kg
Package Level 1 Height:	87 mm
Package Level 1 Length:	177 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	135 mm
Package Level 2 Height:	200 mm
Package Level 2 Length:	300 mm
Package Level 2 Units:	30 piece
Package Level 2 Width:	200 mm
Package Level 3 Units:	2880 piece
Pollution Degree:	3
Product Main Type:	D95/26
Product Name:	Terminal block
Product Net Depth:	72 mm
Product Net Height:	87 mm
Product Net Weight:	215 g
Product Net Width:	26 mm
Product Packing Type:	Box
Rated Cross-Section:	95 mm ²
Rated Current (I _n):	Main Circuit 232 A
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 11400 A
Rated Voltage (U _r):	1000 V
Recommended Screw Driver:	6 mm
Selling Unit of Measure:	piece
Spacing:	26 mm
Sub-Function:	2 connections
Sub-Function 2:	Closed block with partition
Sub-Function 3:	2 connections
Sub-Function 4:	Closed block with partition
Tightening Torque:	acc. IEC 60947-1 9 N·m Manufacturer 9.5 N·m
Wire Stripping Length:	26.0 mm
cUL Certificate:	1SND161009A0202

